Numerical Investigation the Effect of the Different Tip Vanes on the Loading of an H-VAWT

Li Shoutu^{1,3}, Wang Yin^{1,3}, Yang Congxin^{1,3}, and Li Ye ^{2,*}

¹ School of Energy and Power Engineering, Lanzhou University of Technology, Lanzhou 730050, China

² School of Naval Architecture, Ocean and Civil Engineering, Shanghai Jiao Tong University, Shanghai 200240, China

³ Key Laboratory of Fluid machinery and Systems, Lanzhou 730050, China

Abstract. In this paper, the effect of the three typical tip vanes on the loading of an H-VAWT is investigated by employing the three-dimensional unsteady numerical simulation method. The results show that the both transient tangential force coefficient (C_T) and normal force coefficient (C_n) have obvious change when the winglet and the V type vane is used at the blade's tip, respectively. However, in three tip vanes, the C_T average value is the lowest and the C_T fluctuation characteristic is the highest when the winglet is used. Although the winglet and V type vane contribute to change the transient C_T and C_n , the normal force is increased too, it results in increasing fatigue loading and decreasing lifetime for H-VAWT. By comparison, the effect of the plate vane on the loading is weaker. Additionally, the winglet is advantage to improve power coefficient in the low tip speed ratio.

1 Introduction

The potential advantages of Vertical Axis Wind Turbine (VAWT) are continuously explored with developing of wind energy technology. A large number of studies [1][2] have shown that VAWT is suitable for developing green buildings and urban areas with complex wind conditions. However, compared with Horizontal Axis Wind Turbine (HAWT), the VAWT has low efficiency. Therefore, many of VAWT configurations and advance technologies are employed to overcome this question [3][4]. Among these approaches, the influence of finite wing on the aerodynamic characteristic of VAWT is considered mainly [5][6]. In past researches, increasing tip device is an effective method to reduce the effect of tip vortex on VAWT. According to the literatures, the classical tip devices, mainly including winglet and elliptic endplate of different configuration, are widely used in aviation because they have the potential advantage of reducing induce drag by reducing tip loss [7]. For example, Elham A and Van Tooren MJL [8] optimized the aerodynamic and structural characteristics of wing to balance between the minimum drag and minimum weight of wing. Narayan G and John B [9] studied the tip vortex structure induced by the winglet of the subsonic wings, and the results show that the winglet is more suitable for the lower aspect ratio wings.

With the development of wind turbine technology, some of researchers have turned their attention to the effects of different tip devices on the performance of wind turbines. Shimizu Y [10][11] studied the configuration of tip vane (Mie-Type Tip Vane) that was installed on blades of HAWT, and obtained the optimal

configuration of tip vane. Meanwhile, the literature shows that the power output of HAWT could be improved by adding tip vane. Compared with HAWT, the tip device is rarely applied to VAWT. The literature [12] shows that the start-up performance of VAWT is improved by installing winglet at both ends of its blades, but this literature did not describe research process in detail, including the shape of winglet and experimental approach.

Additionally, numerical simulation method is considered as a potential research technique on the H-VAWT [13]. The Shear Stress Transport (SST) $k-\omega$ transitional turbulence model has more accurate results compared with the other fully turbulence model because it could capture the flow separation phenomena [3][14]. Although LES and RANS-LES turbulence model are also regarded as good turbulence model, the computational efficiency is lower compared with $k-\omega$ SST model.

The tip device is widely employed on the blade of wind turbine by method of computationally and experimentally. However, the lots of literatures show that there are a little of researches to discuss the effect of tip device on the loading of VAWT compared with HAWT.

Therefore, in present study, we investigate effect of three different tip devices on the loading of VAWT by employing three-dimensional unsteady numerical simulation method.

2 Numerical methods

* Corresponding author: ye.li@sjtu.edu.cn

In this paper, we employ the 3D computational domain to analyze loading of the single blade H-VAWT when three different tip vanes are installed on the blade tip, respectively. The blade of H-VAWT is composed by NACA0012 airfoil [15], where the chord length (C) is 91.4mm, the blade length (L) is 910mm, the rotor diameter (D) is 1220mm.

2.1 Description of different tip vanes

Fig.1 shows the sketches of the plate vane, V type vane and winglet. The detailed parameters of the three types of blades are shown in Table 1. Moreover, the thickness of V type vane and plate vane are 1mm, it aims to reduce the effect of the vane itself on the contents of researches.

2.2 Geometry and boundary conditions of fluid field

Fig.2 shows the schemes of geometry and the boundary conditions of the numerical simulation for H-VAWT, where the D is the diameter of rotor. The inlet is set as velocity inlet and the distance is $10D$ away from the axis of the rotor, and the free stream wind velocity is 12m/s. The outlet is set as outflow and the distance is $20D$ away

from the axis of the rotor. The walls of airfoil are set as non-slip wall. The all of walls of the rotor that are existed between the rotor and far field are set as interface. The coordinate system is set as rotating coordinate system. The standard atmosphere characteristics are used in simulated flow field, including pressure, density and dynamic viscosity.

In present work, the first layer of grid cells has a height of 0.03 mm and a growth rate of 1.16 to satisfy a Y^+ value of less than 5.

Table 1. Parameters list of tip vane

parameter	value	unit
R1	20	mm
R2	15	mm
A	45	mm
B	73.1	mm
C	73.1	mm
D	25	mm
E	10	mm
α	20	°
β	15	°
L	60	mm
R3	70	mm
θ	60	°

Fig.1. Sketch of three different tip vanes

Fig.2. Scheme of geometry and boundary conditions for H-VAWT

Fig.3. The detailed grids around different blades tip

2.3 Turbulence models and simulation setup

The *SST k- ω* turbulence model is employed in this paper. The spatial and temporal discretization are achieved by considering second order schemes. The continuity equations and momentum equations are solved by segregated approach. The pressure-velocity coupling is achieved by considering SIMPLEC scheme. The time step $\Delta t = 0.5\omega^{-1}$ [16] (ω is rotate speed, the unit is rad/s) is adopted.

It is important to ensure the grid-independent in the numerical method. In this paper, the lift-drag ratio (C_L/C_d) of NACA0012 airfoil is investigated when the angle of attack is 5° and the investigated position located at $Z=0$. Fig.4 shows the C_L/C_d at the different of cells number when the angle of attack is 5° . The maximum C_L/C_d of NACA0012 is converged when the total number of cells is greater than 5×10^6 compared with the results of literature [17]. Therefore, the following numerical simulations are achieved with the number of cells between 5×10^6 and 5.7×10^6 .

Fig.4. The C_L/C_d versus the number of cells at the 5° angle of attack

3 Results and discussions

In this section, the results of this paper are described and presented.

3.1 The effect of different tip vane on loading of H-VAWT

The aerodynamic loadings of the H-VAWT with single blade were analyzed by employing the 3D numerical method. The loadings performance were given by the tangential force coefficient (C_T), normal force coefficient (C_n) and torque coefficient (C_M), and they are defined by Equations (1), (2) and (3) respectively.

$$C_T = \frac{F_t}{0.5\rho L C V_\infty^2} \quad (1)$$

$$C_n = \frac{F_n}{0.5\rho L C V_\infty^2} \quad (2)$$

$$C_M = \frac{M}{0.5\rho L C^2 V_\infty^2} \quad (3)$$

Where ρ presented the air density, V_∞ was the free stream velocity, F_t was the tangential force, F_n was the normal force and M was the torque. Which the power coefficient (C_p) was defined by the relating with C_m and tip speed ratio (λ):

$$C_p = C_m \cdot \lambda \quad (4)$$

Fig.5 showed the comparative results of the C_T between the without tip vane and the three different tip vanes on the blade tip of H-VAWT. The effect of the three different tip vanes on the C_T of an H-VAWT was obvious. Moreover, the C_T was increased in a period of rotation for the rotor, especially, in the downstream side of the rotor ($180^\circ \leq \theta \leq 360^\circ$), where θ was the azimuthal angle. The maximum C_T value, at the azimuthal angle 270° , had obviously improve when the tip vanes were used. However, in the regions from azimuthal angle of 180° to 250° , the C_T values of the winglet and V type vane were lower than C_T values of without vane, on the contrary, the plate vane performed better than the other two tip vanes. Additionally, although the C_T values of the V type vane and winglet were higher than the plate vane in the upstream side of the rotor ($0^\circ \leq \theta \leq 180^\circ$), the C_T was negative. While the variable trend of C_T was adverse in the downstream side of the rotor. However, the maximum C_T happened in the upstream side and downstream side of the rotor when the V type vane and winglet was installed on the blade tip, respectively.

Fig.5. The tangential force coefficient at the different of azimuthal angles

Fig.6 showed the results of C_n at the different azimuthal angles. The C_n values of the V type vane and winglet had obvious advantage compared with the plate vane in upstream side of the rotor, and the positive and negative maximum C_n were happened by employing the winglet both in the upstream side and downstream side of the rotor. Moreover, the negative maximum C_n value was happened at the azimuthal angle 270° in a period of rotation for the rotor. However, in the downstream side of the rotor, the C_n variable trend of the V type vane was gentle compared with C_n of the winglet, and the C_n was increased with increasing of the θ from 250° to 315° . Obviously, although the plate vane was advantage for improving C_n , especial in the upstream side of rotor, the influence was not too obvious compared with the V type vane and winglet.

Fig.6. The normal force coefficient at the different of azimuthal angles

The results of the C_m at the different azimuthal angles when the three different vanes are employed as shown in Fig.7. Both in upstream side and downstream side of the rotor, the C_m value of the winglet performed better than the V type vane and plate vane, especially in the upstream side. Moreover, the winglet obtained the maximum C_m value and the modest minimum C_m value. Meanwhile, in the downstream side of the rotor, the plate vane and V type vane kept the almost same of trend of the C_m . However, the C_m of the winglet had the close the C_m values compared with the other two tip vanes when

the θ values from 135° to 225° . Additionally, the starting torque was improved by employing the winglet, while the starting torque was same when V type vane and plate vane were used.

Fig.7. The torque coefficient at the different of azimuthal angle

The comprehensive aerodynamic characteristics were shown in Fig.8. Compared with the C_p of the without vane, the C_p of the winglet performed better than the V type vane and plate vane, especially in the lower tip speed ratio (λ) regions. However, when the λ values were greater than 5, the C_p of the three tip vanes performed the almost same.

Fig.8. The power coefficient versus tip speed ratio

The table2 showed that the average values of C_T , C_m and C_n when the three different tip vanes was installed on the blade tip of H-VAWT, respectively. Moreover, the $AVG. \Delta C_T$ and $AVG. \Delta C_n$ were defined by Equation:

$$AVG. \Delta C_T = C_{T,max} - C_{T,min} \quad (5)$$

$$AVG. \Delta C_n = C_{n,max} - C_{n,min} \quad (6)$$

Here, the $AVG. \Delta C_T$ and $AVG. \Delta C_n$ were employed to illuminate fluctuate of C_T and C_n . Compared with the results of the without vane, the plate vane helped to improve the average C_T value, however, it was disadvantaged for improving the average C_m and C_n values. On the contrary, in terms of improving average C_m values, the winglet performed better. Additionally, the V type vane and winglet had the almost same of average C_n values. Obviously, the values fluctuate of the

C_T and C_n were increased after adding the tip vane, especially was the winglet vane, the $AVG.\Delta C_T$ and $AVG.\Delta C_n$ was increased 116% and 108%, respectively. While the $AVG.\Delta C_T$ and $AVG.\Delta C_n$ of the V type vane was increased 116% and 41.6%, the plate vane was increased 8.3% and 41.6%.

Table.2. The average values of C_T , C_m and C_n when the different tip vanes were used

Force tip vane	Tangential force coefficient		Normal force coefficient		Torque coefficient
	Average	$AVG.\Delta C_T$	Average	$AVG.\Delta C_n$	
Plate vane	0.033	0.13	-0.017	0.17	0.003
V type vane	0.006	0.26	-0.05	0.17	0.005
Winglet vane	0.0004	0.26	-0.06	0.25	0.01
Without vane	0.01	0.12	-0.01	0.12	0

4 Conclusions

In this paper, we investigate the effect of the three classic tip vanes on loading of the single blade H-VAWT by employing 3D unsteady numerical method.

The transient C_T value has obviously changed when the winglet and V type vane is used at the blade's tip, respectively. However, the C_T average value is the lowest and the fluctuation characteristic is the highest when the winglet is used. On the contrary, although the transient C_T is lowest when the plate vane is employed, C_T average value is the highest, while the fluctuation characteristic is the lowest.

In terms of C_n , the effect of the winglet and V type vane on transient C_n are also obvious, moreover, the average C_n value and the fluctuation characteristic are highest when winglet is used. Meanwhile, the V type vane and plate present same of the fluctuation characteristic.

Although the winglet and V type vane help to change the transient C_T and C_n , the tangential and normal force are increased too, it results in increasing fatigue loading and decreasing lifetime for H-VAWT. However, the plate vane is weaker on the effecting loading.

The winglet performs better in terms of improve C_m , moreover, it improves power coefficient in the low tip speed ratio area.

References

1. G. Bedon, S. De Betta, E. Benini, *Renew Energy* **94**, 328–40 (2016)
2. F. Toja-Silva, A. Colmenar-Santos, M. Castro-Gil, *Renew Sustain Energy Rev* **24**, 364–78 (2013)
3. M. Ghasemian, Z.N. Ashrafi, A. Sedaghat, *Energy Convers Manag* **149**, 87–100 (2017)
4. A. Bianchini, F. Balduzzi, J.M. Rainbird, J. Peiró, J.M.R. Graham, G. Ferrara, et al, *Energy Convers Manag* **106**, 373–84 (2015)

5. K.H. Wong, W.T. Chong, N.L. Sukiman, S.C. Poh, Y.C. Shiah, C.T. Wang, *Renew Sustain Energy Rev* **73**, 904–21 (2017)
6. S. Zanforlin, S. Deluca, *Energy* **148**, 179–95 (2018)
7. L.B. Gratzler, Patent - Split Blended Winglet (2014)
8. A. Elham, M.J.L. Van Tooren, *Aerosp Sci Technol* **37**, 93–109 (2014)
9. G. Narayan, B. John, *Aerosp Sci Technol* **58**, 328–40 (2016)
10. Y. Shimizu, T. Yoshikawa, S. Matsumura, *J Fluids Eng* **114**, 293–7 (1994)
11. Y. Shimizu, H. Imamura, S. Matsumura, T. Maeda, *J Sol Energy Eng* **117**, 297–303 (1995)
12. N.A. Ahmed, K.J. Netto, *Applied Mechanics and Materials Vol.607*, 581–7 (2014)
13. P. Fuglsang, C. Bak, *Wind Energy* **7**, 145–62 (2004)
14. M. Raciti Castelli, A. Englaro, E. Benini, *Energy* **36**, 4919–34 (2011)
15. B.T. Webster, An experimental study of an airfoil undergoing cycloidal motion. Texas Tech University (1978) .
16. K. McLaren, A numerical and experimental study of unsteady loading of high solidity vertical axis wind turbines, McMaster (2011)
17. <http://airfoiltools.com/> n.d