Influence of Land Use and Land Cover Change on Land surface temperature

Jing Sun^{1*}, and Jing He¹

¹ Department of Geographic Information Science, Tongling University, Tongling, Anhui, 244061, China

Abstract: The rapid urbanization process has recently led to significant land use and land cover (LULC) changes, thereby affecting the climate and the environment. The purpose of this study is to analyze the LULC changes in Hefei City, Anhui Province, and their relationship with land surface temperature (LST). To achieve this goal, multitemporal Landsat data were used to monitor the LULC and LST between 2005 and 2015. The study also used correlation analysis to analyze the relationship between LST, LULC, and other spectral indices (NDVI, NDBI, and NDWI). The results show that the built-up land has expanded significantly, transforming from 488.26 km² in 2005 to 575.64 km² in 2015. It further shows that the mean LST in Hefei city has increased from 284.0 K in 2005 to 285.86 K in 2015. The results also indicate that there is a positive correlation between LST and NDVI and NDBI, while there is a negative correlation between LST and NDWI. This means that urban expansion and reduced water bodies will lead to an increase in LST.

1 Introduction

With the development of the economy, the urban population has grown rapidly, which has promoted rapid urbanization. Land use and land cover (LULC) patterns have undergone tremendous changes, as well as changes in various biophysical climatic conditions, especially urban land surface temperature (LST) [1,2]. The conversion of LULC (such as wetlands, vegetation, and agricultural areas) to impervious land can greatly affect LST [3]. LST is regularly measured from satellite sensors with medium spatial scale and high temporal resolution (such as Landsat). Generally, the LST data derived from the satellite's thermal infrared (TIR) band is a key variable to understand the impact of changes in LULC caused by urbanization [4]. Spectral indices from remote sensing data can usually provide a comprehensive understanding of the relationship between LST and LULC conditions [5,6]. The most common satellite-derived indicators for estimating the temporal and spatial changes of LST are the normalized difference vegetation index (NDVI), the normalized difference built-up index (NDBI), and the normalized difference water index (NDWI) [7]. Previous studies have analyzed the different relationships between LULC, LST, NDVI, NDBI, and NDWI [7-13]. These results are mainly attributable to the growth and expansion of cities brought about by urbanization and socio-economic development, which affect land use and regional climate change.

This study aims to monitor and analyze the spatiotemporal trends of LULC changes and establish their relationship with the LST changes of Hefei city, China. More specifically, the study seeks to: (a) map and

analyze the various changes in the LULC pattern of Hefei city from 2005 to 2015; (b) study the distribution of LST, NDVI, NDBI, and NDWI of the Hefei city; (c) analyze the relationship of LST and indices (NDVI, NDBI, and NDWI).

2 Materials and Methods

2.1. Study Area

Hefei city is the largest and capital city of Anhui Province, China, which comprises four urban districts, one county-level city, and four counties. In this study, four urban districts were chosen as the study area, which covers an area of 1308 km² and is situated between 116°51'-117°26'E and 31°38'-32°4'N. (Figure 1).

Figure 1. Location map of the study area.

*Corresponding author's e-mail: sunjing@tlu.edu.cn

2.2. Datasets

To identify the changes in LULC, the Landsat 5/7/8 images of Level-1 products for Worldwide Reference System-2 with Path 121 Row 38 on 5 March 2005, 11 March 2010, and 1 March 2015, were downloaded through the United States Geological Survey online portal (www.earthexplore.usgs.gov). Auxiliary data in the form of reference maps were obtained from Google Earth imagery. The MOD05_L2 product of MODIS/Terra on the

same day with the Landsat data was downloaded from LAADS DAAC (<https://ladsweb.modaps.eosdis.nasa.gov/>).

2.3. Research Methodology

The methodological flow chart illustrated in Figure 2 summarizes the several procedures used in this study.

Figure 2. Methodological flow chart of the study.

2.3.1. LULC Classification

The maximum likelihood classification (MLC) method is one of the most widely used LULC classification methods due to its high classification accuracy [14,15]. In this study, the MLC method was used to divide the LULC in 2005, 2010, and 2015 into four categories, including built-up land, agricultural land, forest land, and water bodies.

2.3.2. Accuracy Assessment

The standard thematic accuracy assessment was adopted using overall accuracy (OA), and Kappa hat (KH) coefficient based on error matrix between classified LULC data and ground reference information data [16]. For thematic accuracy assessment, the number of samples was estimated based on the multinomial distribution [16,17], and sample points were allocated for thematic accuracy assessment using a stratified random sampling technique.

2.3.3. NDVI, NDBI, and NDWI Estimation

The NDVI, NDBI, and NDWI are the most used indicators in environmental studies, which were applied to extracting vegetation conditions, impervious surfaces, and water bodies from remotely sensed data, respectively. These indices were estimated using Equation (1) to Equation (3) [7].

$$NDVI = (NIR - Red)/(NIR + Red) \quad (1)$$

$$NDBI = (SWIR1 - NIR)/(SWIR1 + NIR) \quad (2)$$

$$NDWI = (Green - NIR)/(Green + NIR) \quad (3)$$

2.3.4. LST Retrieval

The TIR bands from Landsat 5/7/8 were used to retrieve LST through a single channel (SC) algorithm. The process to retrieve LST is discussed below.

(1) Brightness temperature calculation

DNs of the TIR band of Landsat images were converted to spectral radiance using the radiance scaling factors provided in the metadata file. Then the brightness temperature (BT), which is the effective temperature viewed by the satellite under an assumption of unity emissivity, can be converted from spectral radiance with the following formula [1]:

$$L_{\lambda} = M_L \cdot Q_{cal} + A_L \quad (4)$$

$$T = K_2 \cdot \left(\ln \left(\frac{K_1}{L_{\lambda}} + 1 \right) \right)^{-1} \quad (5)$$

where, L_{λ} is the spectral radiance ($W/(m^2 \cdot sr \cdot \mu m)$), M_L is the radiance multiplicative scaling factor, A_L is the radiance additive scaling factor, Q_{cal} is the pixel value in DN, T is BT in Kelvin (K), K_1 , and K_2 are the thermal conversion constants.

(2) Emissivity extraction

In this study, the NDVI threshold method [18] were adopted to estimate the emissivity of different land surfaces as follows:

$$\varepsilon = \begin{cases} \varepsilon_w & NDVI \leq 0 \\ \varepsilon_s & 0 < NDVI < NDVI_s \\ \varepsilon_v \cdot P_v + \varepsilon_s \cdot (1 - P_v) + (1 - \varepsilon_s) \cdot \varepsilon_v \cdot F' \cdot (1 - P_v) & NDVI_s \leq NDVI \leq NDVI_v \\ \varepsilon_v \cdot P_v + (1 - \varepsilon_s) \cdot \varepsilon_v \cdot F' \cdot (1 - P_v) & NDVI > NDVI_v \end{cases} \quad (6)$$

where, ε is the band emissivity, ε_v and ε_s are the emissivities of vegetation and soil, respectively, P_v is the proportion of vegetation, $NDVI_v$ and $NDVI_s$ are the $NDVI$ for a fully vegetated pixel and a soil one, respectively, and F' is a geometrical factor ranging between 0 and 1.

(3) Water vapor content extraction

MODIS Reprojection Tool and MRTSwath tool were used for reprojection and conversion of MODIS product to DN values of water vapor content. To retrieve the real value of water vapor content, the DN values were divided by the scaling factor (scaling factor = 1000).

(4) Land surface temperature derivation

The SC algorithm provided by Jiménez-Muñoz and Sobrino [19] was chosen for LST retrieval from Landsat data using the following Equation (7):

$$T_s = \frac{T_{sen}^2}{b_\gamma L_{sen}} \left[\frac{1}{\varepsilon} (\varphi_1 L_{sen} + \varphi_2) + \varphi_3 \right] + (T_{sen} - \frac{T_{sen}^2}{b_\gamma}) \quad (7)$$

where, T_s is the land surface temperature, ε is the surface emissivity, T_{sen} is the at-sensor BT; $b_\gamma = c_2/\lambda$; and φ_1 , φ_2 , and φ_3 are the atmospheric functions which can be obtained as a function of the total atmospheric water vapor content (w) [20-22].

3 Results & Discussion

3.1. LULC Classification and Change Detection

The classified LULC maps of Hefei city are presented in Figure 3 and quantified in Table 1. These classes comprise built-up land (B), agricultural land (A), forest land (F), and water bodies (W).

Figure 3. Classified LULC of Hefei city in; (a) 2005, (b) 2010, and (c) 2015.

Table 1. LULC distribution in 2005, 2010, and 2015.

LULC Types	2005		2010		2015	
	Area (sq. km)	Area (%)	Area (sq. km)	Area (%)	Area (sq. km)	Area (%)
Built-up land	488.26	37.31	504.16	38.53	575.64	43.99
Agricultural land	692.84	52.95	651.77	49.81	625.01	47.76
Forest land	21.88	1.67	35.82	2.74	8.14	0.62
Water bodies	105.57	8.07	116.80	8.93	105.33	8.05
Total	1308.56	100.00	1308.56	100.00	1308.56	100.00

The result reveals that the built-up land has expanded from 488.26 km² (37.31%) in 2005 to 575.64 km² (43.99%) in 2015 as the most one among the four LULC types in Hefei city. However, the agricultural land and forest land decreased from 692.84 km² (52.95%) and 21.88 km² (1.67%) in 2005 to 625.01 km² (47.76%) and 8.14 km² (0.62%) in 2015, respectively. Meanwhile, the water bodies remained basically unchanged. The gradual increase in built-up land and decrease in agricultural land can be attributed to urban growth. It can be seen from the LULC classification and change detection that the urbanization process of Hefei may be an important factor in the transition from the natural surface to the built-up land.

3.2. Accuracy Assessment of LULC Classification

In this study, 443 sample points based on the multinomial distribution with the desired precision of 5% and a level of confidence of 85% were applied to access thematic accuracy assessment. Table 2 shows the error matrix and accuracy of LULC classification in 2005, 2010, and 2015. The OA and KH of the three maps were above 87%, and 0.8, which signifies a reliable LULC classification [23].

Table 2. Error matrix of 2005, 2010, and 2015.

(a) 2005 Error Matrix					(b) 2010 Error Matrix					(c) 2015 Error Matrix				
LULC Types	B	A	F	W	LULC Types	B	A	F	W	LULC Types	B	A	F	W
B	59	14	3	2	B	89	13	2	1	B	129	11	5	1
A	4	277	5	4	A	13	239	5	2	A	10	194	4	2
F	3	5	15	2	F	2	4	18	1	F	4	5	15	1
W	1	1	0	48	W	1	2	2	49	W	1	3	0	48
OA	90.1%				OA	89.2%				OA	87.1%			
KH	0.808				KA	0.815				KA	0.802			

3.3. LST Distribution

The spatial distribution of LST of Hefei city in 2005, 2010, and 2015 were illustrated in Figure 4. The results indicate that the LST of Hefei city ranged between approximately 277.45-287.16 K, 272.77-290.66 K, and 279.63-288.86 K in 2005, 2010, and 2015, respectively. Meantime, the mean LST were approximately 284.01, 286.69, and

285.86 in 2005, 2010, and 2015, respectively. The LST analysis indicates that the mean LST of the Hefei city has increased by 2.68 K from 2005 to 2015. Furthermore, the mean LST decreased by 0.83 K from 2010 to 2015 since the data acquisition date in 2015 was 10 days earlier than in 2010. In general, the mean LST in Hefei city increased by 1.85 K from 2005 to 2015.

The development of urban land has led to an increase in land surface temperature in Hefei, which is consistent with previous studies [24].

Figure 4. LST distribution of Hefei city in: (a) 2005, (b) 2010, and (c) 2015.

3.4. NDVI, NDBI, and NDWI Distribution and Their Relationship with LST

The distribution of NDVI of Hefei city in 2005, 2010, and 2015, is presented in Figure 5. The result indicates that the NDVI values ranged between -0.3930 to 0.5963 in 2005, -0.4286 to 0.4790 in 2010, and -0.3610 to 0.6386 in 2015. The results demonstrate the highest NDVI in the west and north-eastern part of Hefei city, mainly covered by forest land and agricultural land. The distribution of NDBI of

Hefei city in 2005, 2010, and 2015 is presented in Figure 6. The result indicates that the NDBI values ranged between -0.8517 to 0.5966 in 2005, -0.6429 to 0.5283 in 2010, and -0.6811 to 0.4768 in 2015. The built-up land in the center of Hefei city has a higher NDBI while the water bodies have a lower NDBI. The distribution of NDWI of Hefei city in 2005, 2010, and 2015 is presented in Figure 7. The result demonstrates that the NDWI values ranged between -0.5022 to 0.4908 in 2005, -0.3846 to 0.4828 in 2010, and -0.5461 to 0.4534 in 2015. Among them, the water bodies have the highest NDWI value.

Figure 5. NDVI spatial distribution of Hefei city in: (a) 2005, (b) 2010, and (c) 2015.

Figure 6. NDBI spatial distribution of Hefei city in: (a) 2005, (b) 2010, and (c) 2015.

Figure 7. NDWI spatial distribution of Hefei city in: (a) 2005, (b) 2010, and (c) 2015.

To examine the relationship between NDVI, NDBI, NDWI, and LST, the correlation was calculated with the Band Collection Statistics tool in ArcGIS and the results are displayed in Table 3. It shows a positive correlation between the values of LST and NDVI and NDBI, and a negative correlation between LST and NDWI. The results indicate that lower LST values corresponded to lower NDVI (e.g., water bodies), while higher LST values

corresponded to higher NDVI (e.g., agricultural land). Furthermore, the results also manifest that lower LST values corresponded to lower NDBI (e.g., water bodies), while higher LST values corresponded to higher NDBI (e.g., built-up land). In contrast, the results imply that lower LST values corresponded to higher NDWI (e.g., water bodies), while higher LST values corresponded to lower NDWI (e.g., built-up land).

Table 3. Correlation between NDVI, NDBI, NDWI and LST

Year	NDVI and LST	NDBI and LST	NDWI and LST
2005	0.4861	0.7726	-0.5903
2010	0.6949	0.6553	-0.7811
2015	0.7123	0.7369	-0.7735

The positive correlation between LST and NDVI, the positive correlation between LST and NDBI, and the negative correlation between LST and NDWI conform to earlier studies. Yuan Chi et al.[8] analyzed relationships among LST and NDVI in the Yellow River Delta, China, the positive correlations were observed in all seasons of 2016–2017. Subhanil Guha et al. [11] focuses on the study of land surface temperature with NDBI using Landsat 8 OLI and TIRS data in Florence and Naples city, and LST performs a strong correlation with NDBI (positive). Bayes Ahmed et al.[25] analyzed LULC and LST in Dhaka, Bangladesh, and the results of multiple correlation and regression analyses indicate that LST presents a negative correlation with NDWI.

4 Conclusions

The multi-temporal Landsat satellite data was used to analyze the spatiotemporal impact of LULC changes on LST in Hefei city from 2005 to 2015 in this study. The

LULC change analysis indicates a rapid urban growth in Hefei city with a considerable built-up land increase from 488.26 km² in 2005 to 575.64 km² in 2015. The LST analysis result revealed that the mean LST increased from 284.0 K in 2005 to 285.86 K in 2015. The correlation between LST and land-use indices was also analyzed in this study. The study suggests a positive relationship between LST and NDBI while establishing a negative relationship between LST and NDWI during the different periods. This implies that higher LST is experienced along with a decline in water bodies and an increase in built-up land. The findings of this study suggest that LULC changes in Hefei city have substantially influenced LST. Consequently, the mitigation plan to reduce land surface temperature due to urbanization should be prepared by the corresponding agencies.

Acknowledgments

This research was funded by the Natural Science Research Project of Anhui Education Department, grant number KJ2019A0707.

Reference

1. Ranagalage, M.; Estoque, R.C.; Handayani, H.H.; Zhang, X.; Morimoto, T.; Tadono, T.; Murayama, Y. Relation between Urban Volume and Land Surface Temperature: A Comparative Study of Planned and Traditional Cities in Japan. *Sustainability* 2018, 10, 2366.
2. Fu, P.; Weng, Q. A time series analysis of urbanization induced land use and land cover change and its impact on land surface temperature with Landsat imagery. *Remote Sensing of Environment* 2016, 175, 205-214.
3. Kafy, A.A.; Rahman, M.S.; Faisal, A.-A.; Hasan, M.M.; Islam, M. Modelling future land use land cover changes and their impacts on land surface temperatures in Rajshahi, Bangladesh. *Remote Sensing Applications: Society and Environment* 2020, 18, 100314.
4. Zhu, Z.; Woodcock, C.E. Continuous change detection and classification of land cover using all available Landsat data. *Remote Sensing of Environment* 2014, 144, 152-171.
5. Fu, P.; Weng, Q. Responses of urban heat island in Atlanta to different land-use scenarios. *Theoretical and Applied Climatology* 2018, 133, 123-135, doi:10.1007/s00704-017-2160-3.
6. Estoque, R.C.; Murayama, Y.; Myint, S.W. Effects of landscape composition and pattern on land surface temperature: An urban heat island study in the megacities of Southeast Asia. *Science of The Total Environment* 2017, 577, 349-359.
7. Chen, X.-L.; Zhao, H.-M.; Li, P.-X.; Yin, Z.-Y. Remote sensing image-based analysis of the relationship between urban heat island and land use/cover changes. *Remote Sensing of Environment* 2006, 104, 133-146.
8. Chi, Y.; Sun, J.; Sun, Y.; Liu, S.; Fu, Z. Multi-temporal characterization of land surface temperature and its relationships with normalized difference vegetation index and soil moisture content in the Yellow River Delta, China. *Global Ecology and Conservation* 2020, 23, e01092.
9. Zhang, Y.; Odeh, I.O.A.; Han, C. Bi-temporal characterization of land surface temperature in relation to impervious surface area, NDVI and NDBI, using a sub-pixel image analysis. *International Journal of Applied Earth Observation and Geoinformation* 2009, 11, 256-264.
10. Yuvaraj, R.M. Extents of Predictors for Land Surface Temperature Using Multiple Regression Model. *The Scientific World Journal* 2020, 2020, 3958589.
11. Guha, S.; Govil, H.; Dey, A.; Gill, N. Analytical study of land surface temperature with NDVI and NDBI using Landsat 8 OLI and TIRS data in Florence and Naples city, Italy. *European Journal of Remote Sensing* 2018, 51, 667-678.
12. Mirchooli, F.; Sadeghi, S.H.; Khaledi Darvishan, A. Analyzing spatial variations of relationships between Land Surface Temperature and some remotely sensed indices in different land uses. *Remote Sensing Applications: Society and Environment* 2020, 19, 100359.
13. Taloor, A.K.; Drinder Singh, M.; Chandra Kothiyari, G. Retrieval of land surface temperature, normalized difference moisture index, normalized difference water index of the Ravi basin using Landsat data. *Applied Computing and Geosciences* 2021, 9, 100051.
14. Shang, M.; Wang, S.-X.; Zhou, Y.; Du, C. Effects of Training Samples and Classifiers on Classification of Landsat-8 Imagery. *Journal of the Indian Society of Remote Sensing* 2018, 46, 1333-1340.
15. Li, C.; Wang, J.; Wang, L.; Hu, L.; Gong, P. Comparison of Classification Algorithms and Training Sample Sizes in Urban Land Classification with Landsat Thematic Mapper Imagery. *Remote Sensing* 2014, 6, 964-983.
16. Congalton, R.G.; Green, K. Assessing the Accuracy of Remotely Sensed Data - Principles and Practices Second edition; CRC Press, Taylor & Francis Group: Boca Raton, NW, USA, 2009; p. 210.
17. Tortora, R.D. A Note on Sample Size Estimation for Multinomial Populations. *American Statistician* 1978, 32, 100-102.
18. Sobrino, J.A.; Jiménez-Muñoz, J.C.; Soria, G.; Romaguera, M.; Moreno, L.G.A.-J.; Plaza, A.; Martinez, P. Land Surface Emissivity Retrieval From Different VNIR and TIR Sensors *IEEE Transactions on Geoscience and Remote Sensing* 2008, 46, 316-327.
19. Jiménez-Muñoz, J.C.; Sobrino, J.A. A generalized single-channel method for retrieving land surface temperature from remote sensing data. *Journal of Geophysical Research* 2003, 108, ACL 2-1.
20. Sobrino, J.A.; Jiménez-Muñoz, J.C.; Paolini, L. Land surface temperature retrieval from LANDSAT TM 5. *Remote Sensing of Environment* 2004, 90, 434-440.
21. Jiménez-Muñoz, J.C.; Cristobal, J.; Sobrino, J.A.; Soria, G.; Ninyerola, M.; Pons, X. Revision of the Single-Channel Algorithm for Land Surface Temperature Retrieval From Landsat Thermal-Infrared Data. *IEEE Transactions on Geoscience and Remote Sensing* 2009, 47, 339-349.
22. Jiménez-Muñoz, J.C.; Sobrino, J.A.; Skoković, D.; Mattar, C.; Cristóbal, J. Land Surface Temperature Retrieval Methods From Landsat-8 Thermal Infrared Sensor Data. *IEEE Geoscience and Remote Sensing Letters* 2014, 11, 1840-1843.
23. Story, M.; Congalton, R.G. Accuracy Assessment: A User's Perspective. *Photogrammetric Engineering and Remote Sensing* 1986, 52, 397-399.
24. Roustai, I.; Sarif, M.O.; Gupta, R.D.; Olafsson, H.; Ranagalage, M.; Murayama, Y.; Zhang, H.; Mushore, T.D. Spatiotemporal Analysis of Land Use/Land Cover and Its Effects on Surface Urban Heat Island Using Landsat Data: A Case Study of Metropolitan

- City Tehran (1988–2018). *Sustainability* 2018, 10, 4433.
25. Ahmed, B.; Kamruzzaman, M.; Zhu, X.; Rahman, M.S.; Choi, K. Simulating Land Cover Changes and Their Impacts on Land Surface Temperature in Dhaka, Bangladesh. *Remote Sensing* 2013, 5, 5969-5998.