From Flames to Fuels: A Review of Combustion in Energy Generation

M Hari Krishna[1*], *Manjunatha*[2], *Navdeep* Singh[3], *Shiney* M Abraham[4], *Koushal* Dhamija[5], *Laeth* H.J. Hamza[6], *Ravi* Kalra[7]

[1]Institute of Aeronautical Engineering, Dundigal, Hyderabad, India
[2]Department of Mechanical Engineering, New Horizon College of Engineering, Bangalore, India
[3]Lovely Professional University, Phagwara, India
[4]Department of Electrical and Electronics Engineering, Mangalam College of Engineering, Kottayam, Kerala
[5]Lloyd Institute of Management and Technology, Greater Noida, Uttar Pradesh, India-201306
[6]Department of Structurals Techniques engineering, College of Technical Engineering, The Islamic University, Najaf, Iraq
[7]Lloyd Institute of Engineering & Technology, Greater Noida, Uttar Pradesh 201306

Abstract. This review paper delves into the nuanced world of combustion in energy generation, exploring the different kinds and their respective influences and utilization. It spans from complete type to explosive combustion, each imparting specific features, environmental implications, and technological advancements. Complete-type combustion, renowned for its cleanliness, contrasts sharply with the hazardous incomplete combustion. Whereas, rapid combustion is extremely good for enhancing engine performance, and spontaneous combustion is marked by its natural incidence without outside triggers. Explosive combustion, prominent by its rapid response rates, underscores the complexity and risks inherent in certain combustion techniques. The paper similarly investigates catalysts, fuel enhancements, and technological innovations aimed toward optimizing combustion performance and reducing environmental detriments. This complete review presents a deep dive into the combustion mechanisms, their utilization, and the ongoing research aimed at mitigating their environmental affects while enhancing efficiency in energy generation systems.

Keyword-: Combustion, types, application, control strategies, Conventional Power Plant.

1 Introduction

The majority of the discussion on the sustainability of energy revolves around clean-energy technologies such as solar power, wind power, and thermal. But along with fossil fuels accounting for nearly 80% of total energy consumption in the USA, combustion maintains the primary mode of energy conversion for power production as shown in Fig.1, electricity,

*Corresponding author: m.22harikrishna@gmail.com

and transportation [1]. The carbon content of a fuel determines how much CO2 is created from it. This content is determined by the hydrogen as well as carbon content of the fuel. Whenever carbon and hydrogen react with oxygen during burning, heat is produced [2]. Methane, a natural gas, has more energy than other fuels and emits less CO2. Because various hydrocarbons have varied hydrogen-to-carbon ratios, they create varying amounts of water and carbon dioxide. In general, the carbon-to-hydrogen ratio increases with the length and complexity of the molecule [3]. As a result, the burning of equivalent amounts of various hydrocarbons produces varied amounts of carbon dioxide, depending on the carbon-to-hydrogen ratio in each's molecules. Because coal comprises its longest and complicated hydrocarbon molecules, burning it produces more CO2 than burning the same amount of oil or natural gas. This affects the energy concentration of each of these fuels [4].



Fig. 1: Process of Combustion

Combustion, a reactive oxidation process, converts chemical molecules into energy that is then used for the production of electricity, heating, transportation, and commercial uses. Because of global warming and localized airborne pollutants from petroleum and other petroleum-based combustion research and applications must evolve to achieve carbon neutrality. Understanding chemical reactions is critical for achieving efficient, low-emission processes. Fossil-fuel combustion research provides broad concepts for developing mechanism-based reactions as well as process models. The growth and development of power generating combustion mechanisms from pre-environmental aims to the environmental period (1970-present), with an emphasis on minimizing pollution, clean combustion, and high thermodynamic efficiency in order to fulfill CO2 emission reduction standards. It also addresses the foreseeable future of electricity generation.

2. Types of Combustion

Combustion is a type of chemical mechanism or reaction involving fuel (hydrocarbons) and oxygen (O2). When Hydro-carbons and O2 react, they emit light as well as heat energy. A flammable substance is formed by combining heat and light energy. So, the mathematical equation for the combustion reaction is given in eqn (1):

$$Fuels + O_2 = Heat\ or\ Light\ Energy \quad (1)$$

Combustion is utilized in automobiles, rocket engines, and a variety of other machinery. There are five distinct types of combustion as shown in Fig. 2: complete combustion, in-complete combustion, rapidly combustion, spontaneous combustion, and explosive combustion.



Fig. 2: Types of Combustion

2.1 Complete Combustion

A complete-combustion is one of the several forms of combustion. It happens in an unlimited amount of air, especially oxygen. Additionally, this type of combustion is often referred to as clean combustion. In this combustion, the fuels will undergo combustion entirely with the oxygen, leaving just two by-products: H2O and CO2. The durability and functioning of palladium-based catalysts for methane combustion is investigated in [5]. It shows that PdO is a highly reactive stage, with only minor variances in reactivity rates caused by surface crystalline structure variances. Support has a minor effect on PdO activity, with neutral, acidic, and redox-active supports all producing equal rates. The addition of steam causes a drop in rates owing to coverage impacts rather than architectural or phase alterations. To improve the functioning and durability of Pd-based catalysts, approximately enhance the overall surface of the supported PdO stages while limiting severe water adsorption. Because of their harmful effects on the health of humans and the environment, the establishment of long-lasting and effective catalysts for elimination of air contaminants such as carbon monoxide, CH4, and volatile organic compounds is critical [6]. The latest developments in catalyst stability, comprising endurance over time, sinter obstruction, and multi-impurity tolerance, are offered. The catalytic efficacy of Co3O4 catalysts for complete CH4 combustion was investigated in [7] at various pH levels. This catalyst performed best owing to greater ATetrahedral/AOctahedral and Oads/Olatt proportions while exhibiting the least extent of surface and largest crystalline dimension. The concentration of Co2+ at Tetrahedral locations, as well as surface oxygen molecules that are active, have a considerable impact on CH4 combustion activity.

2.2 Incomplete Combustion

When the amount of air available is limited, incomplete-combustion occurs. As well as in comparison to complete combustion, it is additionally known as filthy combustion. Because of a shortage of O2, the fuel will not fully react. This, in turn, generates CO and carbon instead of CO2. Incomplete-combustion can be reduced by employing biomass content as a reburning fuel, that can yield nitrogen-containing aromatic substances.

The study conducted in [8] explores the heterogeneous interaction among biomass content and NO/O2 gases, which results in the development of nitrated structures and N-aromatics such as nitro-PAH. More research should be conducted on sustainable fuels such as non-charring polymers in order to reduce the toxicity and bio-accumulative qualities of these by-products. A photo-catalyst with a dual Z-scheme of NiO, NiFe2O4, and Fe2O3 was used to produce methylene blue and H2. The photocatalytic breakdown of methylene blue and concomitant hydrogen generation were investigated in [9]. The ability to recover of ten ultrashort-, short-, and long-chain unsubstituted perfluoroalkyl acids (PFAAs) was assessed using two methods: adsorbable organic fluorine (AOF) and extractable organic fluorine (EOF). The total recovery varied from 9.3%-103.3% to 21.0%-108.1%, with larger recovery attempts for PFAAs with longer chains. The study in [10] discovered that the EOF technique is more suited for detecting TOF in samples including ultrashort- and short-chain PFAAs, and technological improvements may be achieved by concentrate on the being washed, elimination, and combustion stages.

2.3 Rapid Combustion

Another form of combustion is rapid combustion. Rapid power requires exterior energy in the form of heat for a reaction to take place. The combustion process generates a tremendous quantity of heat and light power, and it does so quickly. The combustion will continue until such time as fuel is accessible. Rapid combustion enhances engine efficiency and knocking tendencies in a heavily modified engine with a twin spark system [11]. The results reveal that synchronized double spark ignition improves the power generated and efficiency of thermal energy. Knock intensity is dependent on spark timing, and premature emission of heat can lessen exploding pressure along with knock intensity. Supplementary spark is beneficial at minimizing knock intensity if it is placed near to the automatic ignition orientation. CuO and ZnO nanoparticles have been produced using the combustion process in [12], and they have a wide range of uses. When administered to both gram-negative and gram-positive bacteria, the produced nanoparticles demonstrated antibacterial activity. The work in [13] introduces magnetic Ni-Mg ferrites as a potential dye adsorbent for methyl blue, a popular soluble in water azo dye. The nano-particles were produced by a fast combustion process and evaluated using a variety of methods. The nanoparticles' ability to absorb on methyl blue reached 306.4 mg/g at 900 mg/l. The study additionally glanced at the influence of pH on adsorption and used cyclic voltammetry and electrical impedance spectroscopy. The results presented indicate a wide range of potential applications in dye removal.

2.4 Spontaneous Combustion

As the name implies, combustion happens spontaneously. This indicates that no energy from outside is required to initiate the combustion. It occurs due to its own heating. A material with low-ignition temperatures is being heated and the heat cannot leave.When the temperature rises over the ignition point and there is enough oxygen available, combustion occurs. The interaction of alkali metals with water is one example. Spontaneous combustion is a phenomenon that occurs when coal oxidizes at low temperatures. This process is regulated by temperatures, oxidizing past events, and coal characteristics [14]. The present comprehension of spontaneous combustion is constrained, therefore additional study is needed to identify possible concerns and get a deeper comprehension of this phenomena. Qualitative and mathematical models are implemented to forecast coal's self-heating properties. Coal spontaneous combustion (CSC) is a major concern in coal mining and usage. Various methods have been created to prevent CSC and improve workplace safety. The review in [15] addresses typical retardants, classifying them as physical, chemical, or compound retardants. The pros and downsides of each are explored, encouraging research into more efficient and cost-effective materials. An experimental

furnace weighing 15 tonnes was utilized to investigate coal spontaneous combustion as well as anaerobic conditioning in [16]. The findings revealed that temperature rises slowly below 70°C, as do utilization of oxygen and heat intensity. Anaerobic cooling reduces with temperature, dropping rapidly from 452.7 to 250.0°C. Variability in gas proportions can help forecast coal temperature.

2.5 Explosive Combustion

When reactions happen at a high rate, it causes explosive combustion. The reaction happens when something ignites, producing heat, light, and sound energy. The simplest way to explain it is as an explosion. Some famous examples include firecrackers and the explosion of dynamite. The burning of water based slurries including emulsions-containing diesel fuel, petroleum, coal, and coal residue from processing is now more effective by micro-explosive droplet breakage [17]. Experimental data indicate that micro-explosive the atomization procedure can increase environmental efficiency by up to 40%. The utilization of coal-water slurries including petrochemicals has demonstrated a greater relative efficiency indicator than coal, with a devoid of dimensions slurry fuel productivity coefficient improving by 3- 30%. Combustion diagnostic include a cautious investigation into the chemical explosion modes in compressed reactive flows. The approach measures the roles of reactions of chemicals, dispersion, and its compressibility to explosives modes [18]. The results reveal that compressibility is more important than non-chemical impacts in high-speed flows, and that flame kernel development is controlled by chemical reactions. Compressibility influences explosive modes. The work in [19] shows that the ignition densities of the igniting combination, assuming a uniform adiabatic flame temperature, may be utilized to determine exploding limits of different fuels at atmospheric pressure and temperature, offering a valid estimating approach. According to Table 1, different types of combustion include complete, incomplete, rapid, spontaneous, and explosive. Clean combustion improves engine efficiency but may increase emissions. Improvements include catalyst surface area, sustainable fuel development, by-product reduction, engine configuration optimization, and understanding coal characteristics.

Table 1: Various combustion types comparison

Aspect	Complete Combustion	Incomplete Combustion	Rapid Combustion	Spontaneous Combustion	Explosive Combustion
Definition	Combustion occurring with sufficient oxygen, leaving H2O and CO2.	Combustion in limited oxygen, producing CO and carbon.	Combustion that generates a lot of heat and light quickly.	Combustion occurring naturally without external ignition.	Fast reactions producing heat, light, and sound, akin to an explosion.
Oxygen Requirement	Unlimited, especially oxygen.	Limited availability.	Exterior energy required.	Sufficient oxygen available as heat rises above ignition point.	Ignition leads to rapid reaction.
By-products	H2O and CO2.	CO and carbon.	Depends on the fuel and conditions, generally heat and light.	Depends on material and conditions.	Heat, light, and sound energy.
Environmental Impact	Referred to as "clean combustion".	Known as "filthy combustion" due to partial fuel reaction.	Enhances engine efficiency, potential for increased emissions.	Can lead to unexpected fires and emissions.	High impact, potentially dangerous emissions.

Catalysts and Research	Palladium-based catalysts for methane; need for durable catalysts.	Use of biomass as reburning fuel to reduce toxicity.	Use of CuO, ZnO nanoparticles, and Ni-Mg ferrites for various purposes.	Research focused on preventing coal spontaneous combustion.	Studies on micro-explosive droplet breakage for efficiency.
Key Factors for Improvement	Surface area and water adsorption of PdO stages in catalysts.	Development of sustainable fuels and reduction of harmful by-products.	Optimization of engine configurations and spark timing.	Understanding coal characteristics and oxidation processes.	Optimization of fuel mixtures and combustion diagnostics.
Applications	Methane combustion, air contaminant elimination.	Reduction of toxic by-products in combustion.	Engine performance and efficiency, antibacterial applications.	Preventing coal mine fires, safety improvements.	Enhanced fuel efficiency, diagnostic techniques in reactive flows.
Notable Research Findings	Minor variances in reactivity rates due to crystalline structure.	Nitrated structures and N-aromatics formation from biomass content.	Double spark ignition reduces knock intensity in engines.	Temperature and gas proportion can predict coal temperature.	Compressibility impacts explosive modes more than non-chemical factors.

3. Combustion Processes in Conventional Power Plant

The oxy-combustion process evaluation was established in [20] with a fair baseline of technology, which included cryogenic separation technology and a recycling system. The process was modeled using flow diagrams for the process as well as heat and mass equilibrium, which allowed for requirements, budgeting, and examining operational philosophies. The method had an influence on protection and functioning, and an economic study was conducted to calculate electricity costs per kWh. This type of combustion is a potential CO2 capture method for power plants that provides a lower-cost substitute to oxy-fuel combustion. The effectiveness of it is superior than oxy-CO2 combustion, with lower electricity costs and higher efficiency [21]. This method may be enhanced by raising the concentration of oxygen in oxidants while reducing the surplus oxygen coefficient. However, its power costs rise, and its performance may be improved further by integrating with solar parabolic trough collectors [22]. The combustion effectiveness of coal-fired power stations is critical for both energy production and environmental concerns. Conventional optimization methodologies, including neural network approaches, have difficulties when tackling combustion-related issues like dragging, this can reduce efficiency [23]. The present study in [24-25] introduces a unique technique that combines NSGA II-based optimization for multiple objectives with CFD to reduce or eliminate slagging in coal-fired boiler burners [26-28].

4. Emission Control Strategies in Combustion Systems

The study in [29] investigates variable valve actuation depending combustion based control strategies for improving engine exhaust temperatures, exhaust emissions, and performance [30]. It has a single-cylinder heavy-duty diesel generator that includes a high-pressure common-rail injection of fuel system, high-pressure loop-cooled exhaust gas recirculating, and a variable valve actuator system [31-33]. Although the Miller cycle is successful at

reducing exhaust temperature, it has a detrimental influence on carbon monoxide and unburned hydrocarbon emissions. Combining the Miller cycle using an additional intake intake valve opening approach cuts soot emissions by 82%. The study in [34] examines the impact of various intake techniques on the combustion traits, dependability, and releases of partly premixed charge compression ignition (PCCI) engines using conventional and alternate fuels [35]. It covers a variety of methodologies and variables that can be used by itself or in conjunction to control in-cylinder air temperature, pressure, and combination dispersion, allowing for most effective combustion phasing and heat evacuation rate [29]. The enhanced common rail injection technology improves combustion control by permitting numerous consecutive injections in a single engine cycle. This enables the oxidation of soot without boosting NO releases. Experimental findings were achieved utilizing a system prototype powered by a Fiat 1.9 JTD engine and a single-cylinder engine. Multifaceted modeling was utilized to understand the data [36-37].

5. Conclusion

Comprehending numerous combustion techniques is pivotal for improving energy generation and reducing environmental impacts. Enhancements in catalyst design, sustainable gasoline development, and combustion technology are instrumental in advancing energy efficiency and environmental sustainability. This assessment underscores the significance of persevered research and technological advancements in harnessing the entire capacity of combustion processes in energy technology.

- Various combustion nature from complete to explosive are vital in energy era, every with multiple environmental and operational characteristics.
- Key improvements recognition on catalyst performance, gas sustainability, and combustion management to reduce pollutants and improve energy efficiency.
- Improved studies and technology development are crucial for addressing the challenges posed through special combustion procedures, in particular in optimizing fuel use and decreasing emissions.

References

1. Kohse-Höinghaus, Katharina. "Combustion, chemistry, and carbon neutrality." Chemical Reviews 123, 8 (2023): 5139-5219.
2. Jin, Hanfeng, Wenhao Yuan, Wei Li, Jiuzhong Yang, Zhongyue Zhou, Long Zhao, Yuyang Li, and Fei Qi. "Combustion chemistry of aromatic hydrocarbons." Progress in Energy and Combustion Science 96 (2023): 101076.
3. Girish, K. M., Naik, R., Prashantha, S. C., Nagabhushana, H., Nagaswarupa, H. P., Raju, K. A., ... & Nagabhushana, B. M. (2015). Zn2TiO4: Eu3+ nanophosphor: self explosive route and its near UV excited photoluminescence properties for WLEDs. Spectrochimica Acta Part A: Molecular and Biomolecular Spectroscopy, 138, 857-865.
4. Damodharan, D., Rajesh Kumar, B., Gopal, K., De Poures, M. V., & Sethuramasamyraja, B. (2019). Utilization of waste plastic oil in diesel engines: a review. Reviews in Environmental Science and Bio/Technology, 18(4), 681-697.
5. Chu, H., Feng, S., Hong, R., Ma, X., Qiao, F., & Chen, L. (2024). Effects of ammonia addition on soot formation in hydrocarbon fuels combustion: Challenges and prospects. Fuel, 360, 130569.
6. Gao, L., Tang, A., Cai, T., & Tenkolu, G. A. (2024). Experimental analysis and multi-objective optimization of flame dynamics and combustion performance in methane-fueled slit-type combustors. Applied Energy, 355, 122365.

7. Girish, K. M., Prashantha, S. C., Nagabhushana, H., Ravikumar, C. R., Nagaswarupa, H. P., Naik, R., ... & Umesh, B. (2018). Multi-functional Zn2TiO4: Sm3+ nanopowders: excellent performance as an electrochemical sensor and an UV photocatalyst. Journal of Science: Advanced Materials and Devices, 3(2), 151-160.
8. Öztürk, O., & Taştan, M. (2024). A review of magnetic field assisted combustion. International Journal of Energy Studies, 9(1), 175-198.
9. Karim, H. A. A., & Hannun, R. M. (2024, May). A review of the use of hydrogen gas in internal combustion engines. In AIP Conference Proceedings (Vol. 3091, No. 1). AIP Publishing.
10. Naik, R., Prashantha, S. C., Nagabhushana, H., Sharma, S. C., Nagaswarupa, H. P., Anantharaju, K. S., ... & Girish, K. M. (2016). Tunable white light emissive Mg2SiO4: Dy3+ nanophosphor: its photoluminescence, Judd–Ofelt and photocatalytic studies. Dyes and Pigments, 127, 25-36.
11. Jing, Q., Li, Y., Zhang, L., Wang, D., & Shi, C. (2024). Optimization effect of propylene oxide (PO) on evaporation, combustion, and pollutant emissions of high-energy–density JP-10 fuel. Fuel, 361, 130585.
12. Wang, J., Liu, H., Wei, Z., Pan, K., Ji, W., Jiang, Y., ... & Wang, H. (2024). Mapping the research on the spontaneous combustion of high-pressure hydrogen leakage: A bibliometric analysis. International Journal of Hydrogen Energy, 50, 1006-1028.
13. Rathod, V. P., & Tanveer, S. (2009). Pulsatile flow of couple stress fluid through a porous medium with periodic body acceleration and magnetic field. Bulletin of the Malaysian Mathematical Sciences Society, 32(2).
14. Hosseinzadeh-Bandbafha, Homa, Hamed Kazemi Shariat Panahi, Mona Dehhaghi, Yasin Orooji, Hossein Shahbeik, Omid Mahian, Hassan Karimi-Maleh et al. "Applications of nanotechnology in biodiesel combustion and post-combustion stages." Renewable and Sustainable Energy Reviews 182 (2023): 113414.
15. Paykani, Amin, Hamed Chehrmonavari, Athanasios Tsolakis, Terry Alger, William F. Northrop, and Rolf D. Reitz. "Synthesis gas as a fuel for internal combustion engines in transportation." Progress in Energy and Combustion Science 90 (2022): 100995.
16. Willis, Joshua J., Alessandro Gallo, Dimosthenis Sokaras, Hassan Aljama, Stanislaw H. Nowak, Emmett D. Goodman, Liheng Wu et al. "Systematic structure–property relationship studies in palladium-catalyzed methane complete combustion." Acs Catalysis 7, 11 (2017): 7810-7821.
17. Bhukya, M. N., Kota, V. R., & Depuru, S. R. (2019). A simple, efficient, and novel standalone photovoltaic inverter configuration with reduced harmonic distortion. IEEE access, 7, 43831-43845.
18. Naresh, M., & Munaswamy, P. (2019). Smart agriculture system using IoT technology. International journal of recent technology and engineering, 7(5), 98-102.
19. Masoumi, S., Ashjaee, M., & Houshfar, E. (2024). Laminar flame stability analysis of ammonia-methane and ammonia-hydrogen dual-fuel combustion. Fuel, 363, 131041.
20. Singh, A. S., Vijrumbana, Y., Reddy, V. M., Gadgil, H., & Kumar, S. (2024). Review on NOx Mitigation Techniques for Ammonia Combustion. In Ammonia and Hydrogen for Green Energy Transition (pp. 329-370). Singapore: Springer Nature Singapore.
21. Ramprasad, P., Basavapoornima, C., Depuru, S. R., & Jayasankar, C. K. (2022). Spectral investigations of Nd3+: Ba (PO3) 2+ La2O3 glasses for infrared laser gain media applications. Optical Materials, 129, 112482.
22. Alabi, O. O., Adeyi, T. A., & Ekun, S. K. (2024). Experimental analysis and combustion characteristics of briquettes from different wood in nigeria. Engineering and Technology Journal, 1-8.
23. Goud, J. S., Srilatha, P., Kumar, R. V., Kumar, K. T., Khan, U., Raizah, Z., ... & Galal, A. M. (2022). Role of ternary hybrid nanofluid in the thermal distribution of a dovetail

fin with the internal generation of heat. Case Studies in Thermal Engineering, 35, 102113.
24. Zhang, C., Yan, Y., Shen, K., Xue, Z., You, J., & He, Z. (2024). Comparative analysis of combustion stability and flow performance in micro combustor based on the synergistic action of slotted blunt body and front-baffle. Applied Thermal Engineering, 237, 121802.
25. Yue, L., Jayapal, M., Cheng, X., Zhang, T., Chen, J., Ma, X., ... & Zhang, W. (2020). Highly dispersed ultra-small nano Sn-SnSb nanoparticles anchored on N-doped graphene sheets as high performance anode for sodium ion batteries. Applied Surface Science, 512, 145686.
26. Indira, D. N. V. S. L. S., Ganiya, R. K., Babu, P. A., Xavier, A. J., Kavisankar, L., Hemalatha, S., ... & Yeshitla, A. (2022). Improved artificial neural network with state order dataset estimation for brain cancer cell diagnosis. BioMed Research International, 2022.
27. Jaidass, N., Moorthi, C. K., Babu, A. M., & Babu, M. R. (2018). Luminescence properties of Dy3+ doped lithium zinc borosilicate glasses for photonic applications. Heliyon, 4(3).
28. Lakshmi, L., Reddy, M. P., Santhaiah, C., & Reddy, U. J. (2021). Smart phishing detection in web pages using supervised deep learning classification and optimization technique ADAM. Wireless Personal Communications, 118(4), 3549-3564.
29. Spandana, K., & Rao, V. S. (2018). Internet of Things (Iot) Based smart water quality monitoring system. International Journal of Engineering and Technology (UAE), 7(3), 259-262.
30. Kumar, K. U., Babu, P., Basavapoornima, C., Praveena, R., Rani, D. S., & Jayasankar, C. K. (2022). Spectroscopic properties of Nd3+-doped boro-bismuth glasses for laser applications. Physica B: Condensed Matter, 646, 414327.
31. Jisha, P. K., Prashantha, S. C., & Nagabhushana, H. (2017). Luminescent properties of Tb doped gadolinium aluminate nanophosphors for display and forensic applications. Journal of Science: Advanced Materials and Devices, 2(4), 437-444.
32. Alrobei, H., Prashanth, M. K., Manjunatha, C. R., Kumar, C. P., Chitrabanu, C. P., Shivaramu, P. D., ... & Raghu, M. S. (2021). Adsorption of anionic dye on eco-friendly synthesised reduced graphene oxide anchored with lanthanum aluminate: Isotherms, kinetics and statistical error analysis. Ceramics International, 47(7), 10322-10331.
33. Kulandaivel, D., Rahamathullah, I. G., Sathiyagnanam, A. P., Gopal, K., & Damodharan, D. (2020). Effect of retarded injection timing and EGR on performance, combustion and emission characteristics of a CRDi diesel engine fueled with WHDPE oil/diesel blends. Fuel, 278, 118304.
34. Hora, S. K., Poongodan, R., De Prado, R. P., Wozniak, M., & Divakarachari, P. B. (2021). Long short-term memory network-based metaheuristic for effective electric energy consumption prediction. Applied Sciences, 11(23), 11263.
35. Raj, T. V., Hoskeri, P. A., Muralidhara, H. B., Manjunatha, C. R., Kumar, K. Y., & Raghu, M. S. (2020). Facile synthesis of perovskite lanthanum aluminate and its green reduced graphene oxide composite for high performance supercapacitors. Journal of Electroanalytical Chemistry, 858, 113830.
36. Feng, Yuan, Yuxi Liu, Hongxing Dai, and Jiguang Deng. "Review and perspectives of enhancement in the catalytic stability for the complete combustion of CO, CH4, and volatile organic compounds." Energy & Fuels 37, 5 (2023): 3590-3604.
37. Zheng, Yifan, Yan Liu, Huan Zhou, Wanzhen Huang, and Zhiying Pu. "Complete combustion of methane over Co3O4 catalysts: Influence of pH values." Journal of Alloys and Compounds 734 (2018): 112-120.