

Prospects of using working water reservoirs in the irrigation mode in the development of the hydro energy industry

Aybek Arifjanov¹, Sardor Xoshimov^{1,}, Farrukh Babajanov¹, Dilshod Matkaziye², and Sheroz Komilov¹*

¹National Research University “Tashkent Institute of Irrigation and Agricultural Mechanization Engineers”, Kari Niyazov 39, 100000, Tashkent, Uzbekistan

²Tashkent University of Architecture and Civil Engineering, Yangi-shahar street-9A, Tashkent, Uzbekistan

Abstract. This article presents the countries of the world that use water energy, the world's largest hydropower plants, indicators of water energy reserves utilization, and the importance of irrigation reservoirs in the development of the hydropower industry. There are about 70 reservoirs in operation in our country, and these reservoirs are a huge reserve for the development of the hydropower industry. According to the principle of operation, modern hydro turbines are able to work with low effort and consumption. A micro-hydroelectric power station was built to generate electricity using the Chartak reservoir. The number of Micro HPP units is 3, the units consist of a vertical pipe and a generator. The aggregates are imported from China and are capable of producing a certain amount of electricity if the consumption is 1 m³/s. When calculating aggregates, the working effort was 34 meters, the water consumption of all aggregates was 3 m³/s. Currently, this micro-hydroelectric power station supplies residents of Namangan region and some industrial facilities with electricity. In terms of the efficiency of the Micro HPP, the Turbine Generator useful working coefficient (UWC) is 81%, the Generator UWC is 91% and helps to alleviate the shortage of energy resources and the sustainable development of the economy.

1 Introduction

Energy plays an important role in the life of people and society, it allows to increase the possibilities of satisfying their various needs. The development of human civilization has always been closely related to the amount and types of energy used. The reason for the global tragedy that is unfolding before the eyes of the present generation is that during the 20th century, especially in the last 40 years, the amount of energy used by people for the purpose of economic development has greatly increased. This has a negative impact on the

* Corresponding author: xoshimov.50907@gmail.com

environment. Because the global warming of the climate is directly related to the gases released into the atmosphere by the growing number of internal combustion engines, resulting from the operation of thermal power plants using organic types of fuel. In the next 40 years, more organic fuels were extracted than in the entire history of mankind [1,2]. The current centenary is no exception. However, the resources of these fuels are decreasing due to their processing and use. If the established traditional methods of providing energy and the current rapid development of the economy, the negative impact of the population increase on the environment are maintained, it is inevitable that the consumption of energy resources will be required to increase accordingly. Environmentally clean energy technologies are not able to significantly influence the solution of this problem. The hydropower potential of rivers, reservoirs and irrigation canals, solar, wind energy, biomass (including energy obtained from the use of household waste), energy of rising water and ocean waves, geothermal energy is expressed in alternative forms of energy. In theory, renewable energy sources provide great opportunities for their large-scale use. However, the financial costs associated with this and the conditions that must be met for the production of such energy reduce the attractiveness of these sources to some extent [3-5].

Renewable energy sources are widely used in many countries of the world, including Uzbekistan. Hydropower, one of the oldest and most reliable sources of renewable energy, plays a crucial role in meeting the world's electricity demand. Reservoirs, large artificial lakes formed by damming rivers, are an integral component of many hydropower systems. This paper examines the importance of reservoirs in hydropower generation, highlighting their multifaceted role in ensuring a sustainable and efficient energy supply [6].

One of the main tasks of reservoirs in hydropower is water storage. These man-made reservoirs act as massive batteries, storing excess water during periods of low electricity demand and releasing it when demand is high. Such storage capacity allows hydropower plants to regulate water flow and provide a stable and reliable source of energy. The ability to store water allows hydropower facilities to respond quickly to changes in electricity demand, making them an ideal choice for balancing the grid [7].

To conclude from the above, water reservoirs are of great importance in the development of the hydropower industry. Unlike other renewable sources such as intermittent solar or wind, hydropower from reservoirs is a facility that can produce electricity continuously, serving as a stable and reliable source of energy [8].

As you know, apart from generating electricity, reservoirs also play an important role in flood control and water management. By controlling the flow of rivers, dams and reservoirs, they help prevent downstream flooding during periods of heavy rainfall or rapid snowmelt. This dual-purpose infrastructure not only produces clean energy, but also mitigates the effects of extreme weather events and contributes to the sustainable management of water resources. If these tasks are well studied theoretically and practically, and the available opportunities are used wisely, that is, if the water reservoirs in the irrigation regime are fully adapted to the use of hydroelectric power stations, it will help to alleviate the shortage of energy resources in the republic [9-11].

2. Materials and Methods

2.1 Study Area

Natural field research was conducted in Chartak reservoir. The Chartak Reservoir is located in the north-eastern part of Namangan region and is used to supply water to 5.1 ha. of cultivated areas of the region and to ensure the safety of the population during floods. The full water capacity of Chartak reservoir according to the project is 30 mln.m³, useful water

capacity is 28.6 mln.m³ and, accordingly, the useless volume is 1.4 mln.m³. It is known that reservoir rivers regulate the flow according to seasons and years, and along with canals and other water transfer structures, they provide an opportunity to redistribute the flow across regions [12,13]. Chartak Reservoir is located in the foothills, the length of the reservoir is 4.2 km, the height of the dam is 45 m, and the length of the dam is 1.5 km. The geographical location of the research object is presented in the figure (1).




Fig 1. Chartak reservoir research area

During the research period, the change of the water level in the reservoir bowl depends on several factors. If water is released from the reservoir based on the demand for water alone, it is a process that depends on the amount of precipitation in the area. Reservoir capacity is estimated depending on the amount of precipitation. So, depending on the amount of annual precipitation, it is possible to estimate the amount of water collected from the reservoir in which years and the amount of water that will be released according to the demand of consumers for water during the vegetation period [14].

2.2 Materials

Conducting natural field studies was carried out taking into account the hydraulic and hydrological parameters of the reservoir. Hydrometeorological indicators in the Chartak reservoir, water inflow and outflow, water consumption and water levels are determined from the indicators in the gauges [15,22,23].

Based on the statistical analysis of the results of the last measurements carried out in the Chartak reservoir, the working graph of the reservoir was developed (Fig. 2). Using the working graph, it is possible to monitor the change of the design parameters of the reservoir and get information about the useful volume of the reservoir.




Fig. 2. Graph of dependence of water level of Chartak reservoir on water volume

It is known that each reservoir has graphs of changes in water volume ($W=f(H)$) and submergence zone ($F=f(H)$) depending on the main design indicators, i.e., the water level at the top of the reservoir. Both of these indicators are mainly directly related to the dynamics of reservoirs being filled with mud. After several years of use, it is becoming clear that a significant change has occurred in the design ($W=f(H)$) graph. This situation, firstly, leads to an error in drawing up a plan for supplying water from reservoirs to the national economy, and secondly, it causes an incorrect determination of the reserve part intended for controlling floods and torrents. Also, the filling of the useful volume zone with turbid sediments leads to the change of $F=f(H)$, the increase of the water burial zone. It should be noted that the timely detection of changes in the $W=f(H)$ graph of water reservoirs allows for the correct assessment of the operation mode of the facility. [16,17]. In addition, this graphic plays a special role in the management of the water reservoir and affects the operation mode of the hydroelectric power station.

We can happily say that the energy sector is being developed on a large scale in our country. Not limited to hydrocarbons such as oil and gas, solar, wind and hydroelectric power generating facilities are being built. In particular, in 2017, the joint-stock company "Uzbekhydroenergo" was established by the decree of the President. In the past period, 11 new hydroelectric power stations were built and 8 were modernized. As a result, an additional capacity of 244 megawatts was created. However, only 50 percent of the hydropower potential of our country has been used. Therefore, 21 large projects with a total capacity of 740 megawatts have been developed. In particular, it is planned to implement 7 projects of 170 megawatts next year, 12 projects of 150 megawatts in 2023-2024, and 2 projects of 420 megawatts in 2025-2026. In order to effectively organize these works and further develop the sector, the decision of the President of the Republic of Uzbekistan dated March 30, 2023 "On measures to further reform the hydropower sector" № decision of president (DP)-104 was adopted. The main task of the document is to increase the total capacity of hydropower to 4,9 MW by 2030. The classification of hydroelectric power stations according to the energy production capacity is presented in Table 1 below.

Table 1.Hydroelectric power plants according to energy production capacity

type of HPP	HPP capacity
Huge (unique)	>500 MW
Big	100....500 MW
Medium	15....100 MW
Small power	1....15 MW

Small hydroelectric power stations	Mini	From 100 kW to 1 MW
		From 5 kW to 100 kW
	Pico	From 100 Watt to 5 kW

According to our analysis, it became clear that water energy and other types of renewable energy sources are not being used sufficiently in the countries of the world today [18]. The indicator of the use of water energy among the countries of the world is shown in the table below Table 2.

Table 2. The indicator of the use of water energy among the countries of the world

Name of countries	Technical potential, MW	Mastery status,	
		MW	%
India	11914	2119	17,8
Japan	10270	3545	34,5
Norway	7676	2248	29,3
Italy	7073	3173	44,9
USA	6366	3676	57,7
France	2615	2021	77,3
Spain	2185	2104	96,3
Germany	1830	1826	99,8
Austria	1780	1568	88,1
Sweden	1280	1280	100
Switzerland	859	859	100

Analyzing these data, the countries with the highest energy reserves are listed, but the utilization rate of this reserve is low in most countries. Table 3 below shows the world's largest hydropower plants.

Table 3. The largest hydroelectric power plants in the world (by capacity)

№	Country	Name of HPP	Power (MW)
1	China	Three Gorges	22500
2	Brazil and Paraguay	Itaipu	12000
3	Venezuela	Guri	10200
4	Brazil	Tukurui	8370
5	USA	Grand Kuli (Grand Coule)	6809

Table 4. Indicator of use of renewable energy sources of the countries of the world (2020)

№	Types of energy	Power, GW	Usage indicator, %
1	Water energy	1096	54,3
2	Solar photovoltaic energy	303	15,0
3	Solar thermodynamic energy	4,8	0,2
4	Wind energy	487	24,1
5	Geothermal energy	13,5	0,67
6	Bioenergy	112	5,55
Total:		2016,3	100

2.3 Methods

Depending on the amount of water balance constituents in the reservoir, it is possible to determine the rate of water exchange, the dynamics of mineral substances, discharges and sediments [22,23].

As stated above, when estimating the useful volume of the reservoir and the volume of water in the reservoir, it is necessary to calculate the exact amount of the main quantities in the water balance equation. We write the reservoir water balance equation in the following form [20]

$$W_1 + W_2 + P_n - E_n - V_1 - V_2 + \Delta W_n + S = 0, \quad (1)$$

The input and output components that make up the water balance change depending on the wet or dry period of the year during the use of the reservoir. In addition, water losses in reservoirs, i.e., water losses due to absorption, evaporation, transpiration, and equipment failure, are also affected. [20,21].

Drawing a conclusion from the above analysis, a graph of annual changes of the elements that make up the input and output components of the water balance of the Chartak reservoir was drawn (Fig. 3).




Fig. 3. Interannual changes of the elements of the water balance of Chartak Reservoir

From this graph, we can see that the changes in the input and output elements of the water bank over the years are consistent. Of course, it is necessary to take into account the water balance, pressure, water consumption of the reservoir in the design, construction and operation of hydroelectric power plants [19,21-28].

The static pressure of water reservoirs is important in the operation of hydroelectric power plants. Static head pressure is the difference between the upper and lower water levels and is determined by the following formula.

$$H_{st} = \nabla_{upstream} - \nabla_{downstream} \quad (2)$$

If the static head pressure of the HPP is up to 15 m, the minimum static head pressure is assumed to be equal to the calculated pressure, i.e:

$$H_{accounting} = H_{st, min} \quad (3)$$

if the static head pressure is more than 15 m, then it is determined by the following formula:

$$H_{accounting} = \Sigma H_{st} / 12 \quad (4)$$

HPP and turbine working power is equal to the following:

$$H = H_{accounting} - \Delta h, \tag{5}$$

where $\Delta h = (H_{accounting} \cdot 0.01)$ is equal, are the pressure losses up to the turbine.

When designing a hydroelectric power station, reservoir head pressure and output water consumption are the most important factors in turbine power and energy production. The power on the turbine shaft is determined as follows:

$$N_T = 9.81 \cdot Q_T \cdot H \cdot \eta_T \tag{6}$$

And the total power at the output of the generator is determined by this expression:

$$N_g = N_T \cdot \eta_g = 9.81 \cdot Q_T \cdot H \cdot \eta_T \cdot \eta_g \tag{7}$$

where: $\eta_{HPP} = \eta_T \cdot \eta_g$ HPP is the useful working coefficient.

HPP capacity is calculated as the total amount of energy produced by calculating the capacity of all aggregates known as installed capacity.

$$\mathcal{E} = N_{HPP} \cdot T, \text{ kWh}. \tag{8}$$

3 Results and discussion

As stated above, the decision of the President of the Republic of Uzbekistan № PQ-104 sets the main task of increasing the total capacity of hydropower to 4.8 MW by 2030. In particular, it is planned to build a cascade of Norin hydroelectric power stations with a total capacity of 225 MW on the Norin River in Namangan region. Table 5 below shows the indicator of hydropower use among Central Asian countries (2018).

Table 5. The indicator of hydropower use among Central Asian countries (2018).

Name of States	Technical potential, billion kWh	Mastery status, %
Tajikistan	143,6	11
Kyrgyzstan	72,9	14
Kazakhstan	61,9	13
Uzbekistan	27,4	25
Total	305,8	13,3

From the analysis of data, it can be seen that the possibility of using water energy in our country (technical potential is 27.4 billion kWh), but the indicator of using water energy is 25%. These problems were studied in detail and the decision of the head of state on the development of hydropower was issued. The role of reservoirs in ensuring the implementation of this decision and developing the hydropower network is incomparable. As a result of the reforms carried out in this area and the implementation of the adopted decisions, the Micro HPP with a capacity of 825 kW was built and put into operation in the lower part of the Chartak reservoir (Fig. 4).




Fig. 4. The master plan of the 825 kW MikroGES built on the Chartak reservoir

The discharge pipe of the Chartak reservoir consists of two parts, and this micro-hydroelectric power station is connected to the water source through both discharge pipes. The number of Micro Hydropower unit is 3, the units consist of a vertical pipe and a generator. In the first building (Fig. 5) there are two vertical pipes and the control system is fully automated, the GSM digital mobile system is used for data transmission to control the operation of the generator.




Fig. 5. Scheme of the first building and aggregates

The aggregates are imported from China and are capable of producing a certain amount of electricity if the consumption is $1 \text{ m}^3/\text{s}$. When calculating aggregates, the working pressure is 34 meters, the water consumption of all aggregates is $3 \text{ m}^3/\text{s}$.

The second building (Fig. 6) houses a single vertical pipe, fully automated using a GSM digital mobile system for generator operation and data transmission.




Fig. 6. Scheme of the second building and aggregates

Currently, this micro-hydroelectric power station supplies residents of Namangan region and some industrial facilities with electricity. According to the efficiency factor of Micro Hydropower, Turbine useful working coefficient (UWC) is 81%. Generator UWC is 91%. There are about seventy large and small water reservoirs in use in our country, and these structures serve to raise the hydropower sector to a higher level, as a result, they serve to meet the needs of the population and industrial enterprises for electricity. There are 10 water reservoirs under the jurisdiction of the Water Reservoir Utilization Department of Namangan region alone. These water reservoirs can be considered as the main sources in ensuring the implementation of the tasks specified in the decision DP-104 of the President of the Republic of Uzbekistan dated 30.03.2023 "On measures to further reform the hydropower sector". Of course, if these water reservoirs will be built and put into use, it will make a great contribution not only to the economy of our region, but also to the development of the energy industry.

4 Conclusion

Human civilization and its development have always been closely related to the amount and types of energy used. Energy plays an important role in the life of people and society, meeting their various needs allows to improve the economy. Renewable energy sources are widely used in many countries of the world, including Uzbekistan. Hydropower, one of the oldest and most reliable sources of renewable energy, plays a crucial role in meeting the population's demand for electricity.

To conclude from the above, water reservoirs are of great importance in the development of the hydropower industry. Unlike other renewable sources such as solar or wind, which are intermittent, hydropower from reservoirs allows for continuous generation of electricity that serves as a stable and reliable source of energy. If low-pressure and medium-pressure irrigation regime reservoirs are theoretically and practically studied and fully adapted to the use of hydroelectric power stations, it will help to alleviate the shortage of energy resources in the republic and help to develop the economy in a sustainable manner.

References

1. Petro Lezhnuk, Olexander Rubanenko, Iryna Hunko, *Optimal Management of Small Hydroelectric Plants Power Generation in Local Electrical Systems*. In book: *Advances in Design, Simulation and Manufacturing*. June 2019. DOI:10.1007/978-3-319-93587-4_30
2. Amasi, Aloyce, Wynants, Maarten, Blake, William, Mtei, Kelvin. Journal: *Land*, 2021, Doi 10.3390/land10060638

3. Arifjanov, A., Apakhodjaeva, T., Matkaziyeu, D. *Hydraulic research of the operational water supply tunnel of pskom hydrousel*. E3S Web of Conferences, 2023, <https://doi.org/10.1051/e3sconf/202345202005>
4. R. J. P. Schmitt, S. Bizzi, A. Castelletti, G. M. Kondolf. *Journal: Nature Sustainability*. 2018, doi:10.1038/s41893-018-0022-3
5. Kaletova, T., Arifjanov, A., Samiev, L., Babajanov, F. *Journal of Water and Land Development*, 2022, Pp. 21–26
6. Schleiss, A. J., Franca, M. J., Juez, C., De Cesare, G. *Journal of Hydraulic Research*, 2016, **54(6)**, Pp595–614.
7. Kui Huang, Zhenyu Mu, Xuanyu Shi, Xueshan Ai, Jiajun Guo & Jie Ding. *Comparative Study on Real-Time Economic Operation Algorithm of Three Gorges Hydropower Station*. Lecture Notes in Civil Engineering book series 2023, **356**.
8. Arifjanov, A., Samiyev, L., Xoshimov, S., Shaymardanov, S., Adjiboyev, S. *Transport capacity of flow in earthline channels*. E3S Web of Conferences, (Conmechydro–2023) 2023, **401**, 01020 <https://doi.org/10.1051/e3sconf/202340101020>
9. Altinbilek, D., *International Journal of Water Resources Development*, 2002, vol. **18**, issue 1, 9–24.
10. Yu, T., Guo, S., Liu, P., Li, W0.: *Study on method and application of reservoir flood season staging*. *China Rural Water Hydropower* (**8**), 24–26–36 (2006)
11. Xoshimov, S., Qosimov, T., Ortikov, I., & Hoshimov, A. *IOP Conference Series: Earth and Environmental Science*, 2022, **1076(1)** doi:10.1088/1755-1315/1076/1/012083
12. Cobaner, M., Haktanir, T., Kisi, O., 2008. *Water Resource Manage*, vol. **22**, 757-774.
13. Wild, Thomas B. Loucks, Daniel P. Amundale, George W. *Journal: Journal of Open Research Software*. 2019, Doi 10.5334/jors.261
14. Samiev, L., Shaymardanov, S., Xoshimov, S., Mamadiyorov, O. E3S Web of Conferences., 2023, **452**, 02019 <https://doi.org/10.1051/e3sconf/202345202019>
15. Dmitrieva, K. 2015. Forecasting of a hydropower plant energy production. Østfold University College, Master's Thesis in Computer Science, Halden, Norway, 69p.
16. Juraev, S., Akramov, A., Xoshimov, S., Abdullayev, M. E3S Web of Conferences., 2023, **452**, 06014 <https://doi.org/10.1051/e3sconf/202345206014>
17. Khaydarov, A., Apakxujayeva, T., Atakulov, D. E3S Web of Conferences, (Conmechydro-2023) 2023, **401**, 01013 <https://doi.org/10.1051/e3sconf/202340101013>
18. Liu, Z., Zhang, J., Wen, T., Cheng, J.: *China Rural Water Hydropower* **487(05)**, 124–128 (2023)
19. Arifjanov, A., Sattorov, A., Babajanov, F., Atakulov, D. *Determination of the trajectory of sediment of fluid particles in the forebay of pumping stations*. E3S Web of Conferences, 2023, <https://doi.org/10.1051/e3sconf/202345202020>
20. Abduraimova, D., Rakhmonov, R., Akhmedov, I., Xoshimov, S., Eshmatova, B. *Efficiency of use of resource-saving technology in reducing irrigation erosion*. AIP Conference Proceedings, 2022, 2432 doi:10.1063/5.0089645
21. Latipov, N., Abduraimova, D., Ibragimova, Z., Otakhonov, M., & Hamdamov, M. E3S Web of Conferences, **401**, 03072 (2023)
22. Urishev, B., Nosirov, F., Ruzikulova, N. E3S Web of Conferences., 2023, **383**, 04052
23. Mukhammadiev, M., Dzhuraev, K., Nosirov, F. *Prospects for the Development of the use of Pumped Storage Power Plants in the Energy System of the Republic of*

Uzbekistan Proceedings of International Conference on Applied Innovation in IT, 2023, 11(1), 239–245

24. Abdulkhaev, Z., Madraximov, M., Abdujalilova, S., Mirzababayeva, S., Otakulov, B., Sattorov, A., Umirzakov, Z. (2023). E3S Web of Conferences **452**, 02010
25. Madraximov, M., Abdulkhaev, Z., Qosimov, A., Sirojiddinov, D., Sattorov, A., Arifjanov, A. (2023). E3S Web of Conferences **452**, 02025
26. Abdulkhaev, Z., Madraximov, M., Akramov, A., Arifjanov, A. (2023). AIP Conference Proceedings **2789**, 1
27. Madaliev, M., Chernyshev, S., Ionov, A. (2023). *Numerical Study of Flow after Nasa 0012 Aerodynamic Profile Based on the SST Turbulence Model*. Journal of Construction and Engineering Technology, 20-25.
28. Otakhonov, M., Hoshimov, A., Juraboyev, I., Khujaev, P. (2023). *A Method of Increasing Drainage Flow Transportability in A Drainage Pipeline*. Journal of Construction and Engineering Technology, 26-29.

RETRACTED