

Influence of copolymers of acrylamide and acrylic acid on the structure and water strength of soil

Aziza Abdikamalova^{1,*}, Shakhnoza Kuldasheva¹, Izzat Eshmetov¹, Azamat Boynmuraev², and Bakhodir Kholnazarov³

¹Institute of General and Inorganic Chemistry, Tashkent, Uzbekistan

²Namangan Institute of Engineering and Technology, Namangan, Uzbekistan

³Termez State Universities, Termez, Uzbekistan

Abstract. In this study, the influence of three different hydrolyzed forms of acrylamide and acrylic acid copolymers synthesized at a 5:1 monomer ratio on soil structure were studied. These copolymers were tested on soils of the Karauzyak and Amudara regions of the Republic of Karakalpakstan, which differ in chemical and mineralogical composition and degree of contamination. Commercial water-soluble polymers PAA GS Flokulyant and its hydrolyzed form were used as controls. The main focus of the study was to study the effect of these copolymers on the soil structural coefficient, which is an indicator of the aggregate state of the soil, and on the change in the structural composition of the surface layer of the soil after treatment with polymer solutions. The results showed that the introduction of polymers significantly improves the structural condition of the soil, especially when using hydrolyzed forms of copolymers, which is confirmed by an increase in the structural coefficient and the proportion of mesoaggregates. It was also found that an increase in the concentration of polymer solutions improves the structural characteristics of the soil, this was especially noticeable for potash forms of copolymers, which indicates the high effectiveness of these additives in strengthening the soil structure and improving their agronomic value. In addition, the study showed that soil treatment with polyelectrolytes increases its water retention capacity, which is especially important in conditions of limited water resources.

1 Introduction

Polymers are recognized as effective materials for reducing erosion, improving fertility by creating a stable structure in the soil and sand system [1, 2]. Water-soluble polymers (WSP), due to their unique characteristics, have shown impressive results in protecting soil and water, maintaining moisture and maintaining a loose soil structure [3]. More and more countries and researchers are involved in the work on preventing sand erosion using polymer materials [3, 4].

* Corresponding author: aziza.abdik@gmail.com

Polyacrylamide, polyethylene glycol, polyvinyl alcohol, polyvinylpyrrolidone are especially popular among the used WSP, which are widely used in various industries [5]. The stability of soil aggregates depends on the composition and structural features of the soil, and water-soluble polymers significantly affect the soil structure due to their ability to adsorb water in a volume significantly exceeding their mass. This affects the rate of infiltration, evaporation, density, porosity and structure of the soil system [6].

Tillage with polymer solutions changes the shape, size and nature of adhesion between aggregates. The effectiveness of the interaction of macromolecules with soil particles depends on the surface area of the dispersed soil system [7]. It is observed that the bond of polymers with large soil particles is limited, while adsorption on more dispersed clays is significantly higher [8]. Thus, more significant changes can be expected in soils with a high content of adsorptively active clays compared to sandy soils.

Polyacrylamide (PAA), which is a polymer obtained by polymerization of acrylamide (formed by hydration of acrylonitrile [9-11]), exists in various forms: anionic, neutral and cationic molecules. The structure of PAA can be linear or crosslinked, and linear molecules are soluble in water, unlike crosslinked ones, which absorb water but do not dissolve in it [12]. PAA is used in drinking water purification, paper production, mineral flotation, improving oil production efficiency, stabilizing steep slopes and road slopes, strengthening weak soils, improving load-bearing capacity and preventing soil erosion [13]. The polymer is often used to strengthen weak soils and prevent erosion, being the most commonly used synthetic polymer in geotechnical applications [14]. PAA is effective, inexpensive and requires less to achieve the desired result. Cationic PAA molecules are not suitable for erosion control due to their toxicity to aquatic life, while anionic PAA is less toxic [15].

In recent years, the relevance of research in the field of conservation and improvement of soil fertility has increased significantly against the background of increasing anthropogenic impact and climate change. An important aspect in this field is the study of ways to increase the water resistance of soil aggregates, which directly affects its structural stability, moisture retention capacity and, as a result, the general state of fertility. The use of polyelectrolytes, in particular acrylamide copolymers, represents an innovative approach to solving this problem.

The purpose of these studies is to study the processes of synthesis of the copolymer of acrylamide and acrylic acid in aqueous solutions and to establish the effect of synthesized copolymers on soil characteristics.

2 Experimental work. Material

Three different hydrolyzed forms of acrylamide (AA) and acrylic acid (ACA) copolymers were used in the study, which were synthesized at a monomer ratio of 5:1. The copolymers had the following molecular weight distributions.

Table 1. Molecular weight distributions of copolymers.

Copolymer	The molecular weight of the reaction products, kDa	The content in the system, % by weight.
1AAAK	2700-2800	85
	166	13
	12-15	~2
2AAAK	2900-3000	92
	60	6
	~1	≤2

For comparison, commercial water-soluble polymers PAA GS Flokulyant (Ts 00203849 - 29:2014, "Navoiazot") and its hydrolyzed form with KOH solution at a temperature of 70

°C were selected. For the experiments, the soil of the Karauzyak (SK) and Amudarya (SA) regions of the Republic of Karakalpakstan was used, which differ in chemical and mineralogical composition and degree of contamination.

3 Method

The value of the structural coefficient and the number of water-resistant aggregates were determined by the method [16].

The value of the structural coefficient helps to qualitatively assess the structure of the soil, where a value of more than 1.5 indicates an excellent aggregate state, values from 1.5 to 0.67 indicate a good aggregate state, and indicators less than 0.67 characterize an unsatisfactory aggregate state of the soil. The soil structure coefficient is the ratio between the percentage of mesoaggregates in the soil (0.25≤10 mm) and the total percentage of structural elements of less than 0.25 mm and more than 10 mm in size.

The introduction of polymer solutions (0.4-1.0%) into the soil was carried out by spraying. The consumption of the solution ranged from 100 to 500 kg/Ha.

Table 2. Changes in the structural composition of the surface layer of the soil during processing (dry sieving)*

Sample	C, %	Fraction size (mm), %			C _s **
		≥10	0,25<10	≤0,25	
Water	-	21,8	28,5	42,7	0,40
PAA GS	0,3	23,3	44,4	32,3	0,80
	0,6	16,5	50,2	33,3	0,43
PAA GS ¹	0,3	11,2	42,9	39,9	0,96
	0,6	12,9	56,5	30,6	1,30
1AAAK	0,3	15,5	59	25,5	1,44
	0,6	13,7	47	39,8	0,89
2AAAK	0,3	12,8	46,6	33,6	0,87
	0,6	17,5	49,3	33,2	0,97
1AAAKK	0,3	12,9	59,3	20,8	1,46
	0,6	14,1	63,7	22,2	1,75
2AAAKK	0,3	15,5	63,4	21,1	1,73
	0,6	7,8	72,6	19,6	2,65

* - the consumption of solutions was 200 kg/Ha; ** - the coefficient of structurality. PAA GS¹ – hydrolyzed PAA GS.

Analysis of Table 2 showing changes in the structural composition of the surface soil layer during treatment with various polyacrylamides (PAA) and copolymers of acrylamide and acrylic acid (AA:ACA), reveals important patterns in the effect of these polymers on the soil structure. All treated soils showed a change in the distribution of fraction sizes compared to the control water treatment, while the number of mesoaggregates increased significantly (0.25<10 mm).

Samples treated with hydrolyzed polyacrylamides and copolymers, especially in higher concentrations (0.6%), show a higher percentage of fractions in the range 0.25<10 mm, indicating an improvement in soil structure.

Water as a control showed the lowest C_s (0.40), which reflects the poor aggregate state of the soil. Treatment with polyacrylamides and their hydrolyzed forms improved the structural condition of the soil, as can be seen from the increase in copolymers, especially when using copolymers and their potassium forms (1AAAKK and 2AAAKK), where the

structural coefficient reaches values of 1.46 and 2.65, respectively, at a concentration of 0.6%.

An increase in the concentration of polymer solutions in some cases leads to an improvement in the structural characteristics of the soil (for example, 2AAAKK at a concentration of 0.6% showed C_s 2.65, which is the highest value in the table 3.). However, not in all cases, an increase in concentration contributes to an improvement in C_s , which emphasizes the need to optimize dosages to achieve the best results.

Table 3. Changes in the structural composition of the surface layer of the SK soil during processing (dry sieving)

Sample	C, %	Fraction size (mm), %			C_s^{**}
		≥ 10	0,25<10	$\leq 0,25$	
Water	-	22,60	11,90	65,50	1,14
PAA GS	0,3	21,18	22,32	56,50	0,29
	0,6	15,00	33,80	51,20	0,51
PAA GS ¹	0,3	10,18	40,32	49,50	0,66
	0,6	11,73	47,71	40,56	0,91
1AAAK	0,3	14,09	41,41	44,50	0,71
	0,6	12,00	46,80	41,20	0,88
2AAAK	0,3	18,00	36,40	45,60	0,57
	0,6	15,91	42,09	41,50	0,74
1AAAKK	0,3	18,09	53,91	28,00	1,17
	0,6	9,09	69,39	21,52	2,27
2AAAKK	0,3	14,09	60,36	25,55	1,52
	0,6	7,09	70,61	22,30	2,40

The analysis of Table 3, representing the change in the structural composition of the surface layer of the SK soil after treatment with various polyelectrolytes, shows that all types of tillage led to a decrease in the proportion of small fractions (≤ 0.25 mm) and an increase in the proportion of mesoaggregates (0.25<10 mm), which indicates an improvement in the soil structure compared with control water treatment.

4 The discussion of the results

As in the previous case, significant changes are observed when processing with potassium forms of copolymers 1AAAKK and 2AAAKK, where the percentage of mesoaggregates increases to 69.39% and 70.61%, respectively, at a concentration of 0.6%. The structural coefficient also improved significantly after treatment, especially noticeably when using copolymers with potassium (K), where C_s reaches values of 2.27 and 2.40 for 1AAAKK and 2AAAKK, respectively, at a higher concentration (0.6%). This indicates the high efficiency of these treatments in improving the aggregate state of the soil.

An increase in the concentration of the polymer solution from 0.3% to 0.6% in most cases leads to an improvement in the structural characteristics of the soil, which is reflected in an increase in the proportion of mesoaggregates and an improvement in the structural coefficient.

Both soil samples react to treatment with polymer solutions by improving the structural composition by increasing the proportion of mesoaggregates and reducing the proportion of small and large fractions. However, the degree of variation and the effectiveness of the treatment vary depending on the type of soil and the polymer used.

At the same time, SK soil samples (second soil) show a more pronounced increase in the proportion of mesoaggregates and the coefficient of structurality after treatment compared with SA soil.

A significant improvement in the structural coefficient is observed in SK soil samples after treatment, especially when using potassium forms of copolymers. At the same time, the soil of the SA also shows improvement, but to a lesser extent. This may be due to differences in the initial physical and chemical properties of soils.

An increase in the proportion of mesoaggregates and an improvement in the structural coefficient indicate an improvement in the agronomic value of both types of soils after treatment. However, the SK soil shows more pronounced improvements, which makes it potentially more suitable for agricultural use after treatment with copolymers.

Figure 1 shows the change in the water-resistant aggregates (WRA) of a soil sample of PA when treated with different solutions of polyelectrolytes. It can be seen that with an increase in the concentration of polyelectrolyte solutions (C, %), the percentage of water-bearing aggregates in the soil increases for all the studied samples.




Fig. 1. Change in the WRA of a soil sample during treatment with solutions: 1) PAA GS; 2) PAA GS1; 3) 1AAAK; 4) 2AAAKK; 5) 1AAAKK; 6) 2AAAKK.

Samples 1 and 2 (PAA GS and PAA GS1) show a relatively slower growth of WRA with increasing concentration, while samples 3 and 5 (1AAAKK and 2AAAKK) show a steeper increase in WRA, which may indicate their higher effectiveness in improving the structural properties of the soil. Samples 4 and 6 (1AAAKK and 2AAAKK), where K denotes the potassium form of the polymer, show the highest growth of water-bearing aggregates at all concentrations, which may indicate the presence of potassium, which improves the properties of the polymer in soil structure formation.

It can be assumed that the presence of potassium in polymer chains (in samples 4 and 6) contributes to the formation of cross-links between polymer chains, which improves the formation of water-tight aggregates and contributes to a more effective strengthening of the soil structure [17]. This assumption is supported by the fact that potash forms of polymers show better results compared to their non-potash counterparts.

Thus, the study shows that the use of polyelectrolytes, especially their potassium forms, can be promising for improving the water resistance and structural properties of the soil.




Fig. 2. Change in the WPA of a SK soil sample during treatment with solutions: 1) PAA GS; 2) PAA GS1; 3) 1AAAK; 4) 2AAAKK; 5) 1AAAK; 6) 2AAAKK.

Similar results were also obtained for the SK soil sample, which are shown in Fig. 2. The general trend for all samples is similar: with an increase in the concentration of polyelectrolyte solutions, the percentage of water-resistant aggregates increases. However, compared to the SA soil, the curves in the graph for the SK soil have a lower steepness, which may indicate lower reactivity or different initial conditions of the SK soil. Samples 1 (PAA GS) and 2 (PAA GS1) show the smallest increase in WRA, which is consistent with previous results. While samples 3 (1AAAK) and 4 (2AAAKK) show higher values of WRA at all concentrations.

The most noticeable increase in water-tight aggregates is observed for samples 4 (1AAAKK) and 6 (2AAAKK), where K denotes the potassium form of the polymer. This is consistent with the assumption that potash forms of polyelectrolytes effectively improve the structural properties of the soil.

Differences in the reaction of SA and SK soil samples to treatment with polyelectrolytes may be related to their chemical and mineralogical composition. The soil of the SA contains more clay and sand, but less silt compared to the soil of the SK. This may affect the ability of polyelectrolytes to interact with the soil and form water-bearing aggregates. Clay has a larger surface area and can form more water-tight bonds with polyelectrolytes, while silt can contribute to a more dense packing of soil particles. Sand, having large particles and a smaller surface area, can contribute less to the formation of water-bearing aggregates. Thus, a higher clay content in the soil of SA may facilitate the formation of larger and more water-resistant aggregates compared to the soil of SK, which may explain the higher values of WRA for SA in experimental conditions.

In conditions of limited water resources, research aimed at studying and improving the water retention capacity of soils is becoming especially relevant. Structure-forming additives such as synthetic polyelectrolytes can play a key role in maintaining soil moisture and increasing watering intervals.

The ability of soil to retain water has a direct impact on fertility and productivity, as well as on the resilience of ecosystems to climate change. The effective use of structurants can contribute to an increase in soil moisture reserves, reduce the frequency of irrigation and, as a result, increase the efficiency of water use in agriculture.

The experiments include methods such as determining field soil moisture and centrifugation methods for measuring water retention pressure. The results of the determination of field moisture and structural porosity of the soil are given in Table 4.

Table 4. Structural and porous characteristics of soil samples treated with 2AAAKK*

Sample	ρ_{air} , g/cm ³	ρ_{water} , g/cm ³	ρ_{ben} , g/cm ³	ρ_{ps} , g/cm ³	A_1 , %	A_2 , %	ΣV , cm ³ /g
SK	1,26	2,41	2,78	0,95	0,477	0,658	0,055
SA	1,11	2,18	2,62	0,86	0,491	0,672	0,077

* - the consumption of solutions was 200 kg/ha.

Having studied the structural and porous characteristics of the soil samples of SK and SA after treatment with 2AAAKK solutions, the following changes can be noted compared to the initial untreated soils: the density in air decreased significantly for both samples compared to the initial values (1.71 g/cm³ for SK and 1.56 g/cm³ for SA), indicating a decrease in the total soil compaction and increased porosity after treatment. Air density decreased by 26.3% for SK (from 1.71 to 1.26 g/cm³) and by 28.8% for SA (from 1.56 to 1.11 g/cm³).

ρ_{water} has also decreased, which indicates a decrease in the density of the solid phase of the soil. This may indicate a change in the mineral composition or an increase in pores filled with water.

Densities for benzene and mercury show an increase for treated samples, especially noticeable for SK soil. This may reflect changes in the structure of pores and their distribution, especially in the increase in micropores, which can be filled more efficiently with benzene and mercury.

The percentage of porosity and porosity increased significantly for the treated samples, indicating an improvement in the pore structure and an increase in the proportion of micropores and macropores. For SK, A_1 increased by 43.7% (from 0.332 to 0.477%), and A_2 by 137.6% (from 0.277 to 0.658%). For SA, A_1 increased by 32.3% (from 0.371 to 0.491%), and A_2 by 77.3% (from 0.379 to 0.672%). This improves soil aeration and promotes better water retention. The total pore volume ΣV increased more than 2.5 times for SK (from 0.022 to 0.055 cm³/g) and 9.6 times for SA (from 0.008 to 0.077 cm³/g).

5 Conclusion

The study of the effect of polymer solutions on the soil structure showed that the use of copolymers of acrylamide and acrylic acid significantly improves the aggregate state of the soil, especially at high concentrations. Treatment with polyacrylamides and their hydrolyzed forms increases the coefficient of structurality, which indicates an improvement in the structural characteristics of the soil and contributes to an increase in its agronomic value. Optimizing the concentration of polymer solutions and choosing the appropriate type of polymer are key to achieving the best results. This discovery provides important directions for improving soil structure, important for agricultural applications, especially in conditions of limited water resources.

The study highlights the importance of using polyelectrolytes, especially their potassium forms, to improve soil water retention aggregates. The results demonstrate that the concentration and presence of potassium in polymers significantly affect the increase in the proportion of water-bearing aggregates, which indicates an improvement in the structural properties of the soil. Thus, the use of these polymers can be considered a promising method to increase the effectiveness of strengthening the soil structure. Tillage with polymer solutions leads to a decrease in density and an increase in porosity, which contributes to better moisture retention and aeration. This is important for agriculture, especially in arid conditions where water is a limited resource, and can contribute to increasing yields and ecosystem resilience to climate change.

References

1. Hueso-González, P.; Martínez-Murillo, J.F.; Ruiz-Sinoga, J.D. *Solid Earth* **7**, 1479–1489 (2016)
2. Cao, Y.; Wang, B.; Guo, H.; Xiao, H.; Wei, T. *Ecol. Eng.* **102**, 270–279 (2017)
3. Huang, He and Lihong Liu. “Application of Water-Soluble Polymers in the Soil Quality Improvement.” (2012). 2806
4. I.L.Axmadjonov, A.B.Abdikamalova, A.I.Sharipova, Kh.I. Akbarov, Sh.A.Kuldasheva. //Alinteri Journal of Agriculture Sciences **36(1)**. 356-361 (2021)
5. S.M. Lee, Z.C. Xing, Y.S. Shin, T.H. Gu, B.H. Lee, M.W. Huh, I.K. Kang, *Polym. Korea* **36** 586 (2012)
6. Kuldasheva, S., Jumabaev, B., Agzamkhodjayev, A., Aymirzaeva, L., Shomurodov, K. *Journal of Chemical Technology and Metallurgy* **50(3)**, 314–320 (2015)
7. Chang, Ilhan; Im, Jooyoung; Cho, Gye-Chun, *Sustainability*, **8 (3)**: 251 (2016)
8. Luckham, Paul F; Rossi, Sylvia (1999). *Advances in Colloid and Interface Science*. **82 (1-3)**: 43–92. doi:10.1016/S0001-8686(99)00005-6.
9. Daliri, K.; Pfannkuche, K.; Garipcan, B. *Soft Matter* **17**, 1156–1172 (2021)
10. Pramanik, S.; Dutta, J.; Chakraborty, P. *Indian J. Pharm. Sci.* **83**, 473–482 (2021)
11. Manson, J.; Brabec, M.J.; Buelke-Sam, J.; Carlson, G.P.; Chapin, R.E.; Favor, J.B.; Fischer, L.J.; Hattis, D.; Lees, P.S.; Perreault-Darney, S. *Birth Defects Res. Part B Dev. Reprod. Toxicol.* **74**, 17–113 (2005)
12. Sojka, R.E.; Bjorneberg, D.L.; Entry, J.A.; Lentz, R.D.; Orts, W.J. *Agron.* **92**, 75–162 (2007)
13. Wiśniewska, M.; Chibowski, S.; Urban, T. *Int. J. Environ. Sci. Technol.* **13**, 679–690 (2016)
14. Sojka, R.E.; Entry, J.A.; Orts, W.J.; Morishita, D.W.; Ross, C.W.; Horne, D.J. *Water Sci. Technol.* **51**, 107–115 (2005)
15. Kerr, J.L.; Lumsden, J.S.; Russell, S.K.; Jasinska, E.J.; Goss, G.G. *Environ. Toxicol. Chem.* **33**, 1552–1562 (2014)
16. Zyking N.G. 3 Soil characteristics: tasks for control and self-control of students. (Irkutsk: Udmurt University Publishing House, 2013)
17. Kuldasheva, S., Abdikamalova, A., Abdikamalova, A., Eshmetov, I., ... Nortoziyeva, G. *Investigation of changes in the viscosity properties of acrylamide (co)polymer and their hydrolyzed forms depending on the conditions of their preparation*. *Polymer Bulletin* (2023). <https://doi.org/10.1007/s00289-023-04875-6>.