Deep Learning Forecasting of Renewable Energy Generation Patterns

Manish Nandy[1*], and *Debarghya* Biswas[2]

[1*]Assistant Professor, Department of CS & IT, Kalinga University, Raipur, India
[2]Assistant Professor, Department of CS & IT, Kalinga University, Raipur, India

Abstract. Renewable energy sources, such as wind and solar, are unable to be integrated into present electrical infrastructures due to persistent issues with intermittency and unpredictability. Reliable load pattern forecasting for renewable energy sources and efficient energy storage use are essential for efficient power grid management. For renewable energy data, the intricacies that conventional forecasting techniques, such as autoregressive or statistical approaches, miss include nonlinearities, complicated dynamics, and strong temporal correlations. Forecasting the production of renewable energy sources accurately is therefore vital for optimizing energy storage use and maintaining system stability. This study proposes a CNN-LSTM architecture-integrated deep learning-based forecasting framework to enhance comprehension of the spatial feature representations and temporal correlations in energy and weather historical data. Using real-world wind and solar datasets, the hybrid CNN-LSTM model achieved a prediction accuracy that was 15-22% higher than that of baseline statistical and machine learning approaches such as Random Forest and ARIMA. Innovative dual-stage design combines optimum training approach for non-stationary renewable data with temporal-spatial feature learning to boost flexibility for grid-level deployment. The article also explores the possibilities of Transformers and federated learning frameworks for distributed renewable energy forecasting.

Keywords: Renewable energy, deep learning, time-series forecasting, LSTM, solar power, wind energy, energy prediction

1 Introduction

The growing demand for green and clean energy has propelled the world towards renewable energy such as solar, wind, and hydropower [1]. By switching to renewable energy sources, we may reduce our reliance on finite natural resources and our impact on the environment, two major problems with fossil fuels [2][3]. But, the intermittency, unpredictability, and intermittency of renewable energy sources based on changing weather patterns and seasons as well as uncontrollable geographical factors is one of the main obstacles to incorporating renewable energy into contemporary power networks [4]. Grid balancing, energy storage

* Corresponding author: manishnandy10@outlook.com

scheduling, and supply-demand optimization are particularly difficult due to this heterogeneity; as a result, advanced forecasting systems are crucial for energy planning and operation. So far, conventional methods have formed the basis of renewable energy forecasting [6][7]. The algorithms avoid complicated methods in favor of simpler ones, such exponential smoothing, autoregressive integrated moving average, and statistical regression. Despite the methodologies' useful outputs, they aren't well-suited to the complex, multi-variable, non-stationary nature of data sets pertaining to renewable energy because of how readily they tolerate linear, stationary correlations.

For example, solar generation is based on historic data on irradiance as well as a huge variety of temperature, humidity, and cloud cover interactions. Similarly, wind power prediction suffers from turbulence modeling, wind speed, hyper-variation, and atmospheric pressure changes [8]. All of these, and more, attest to the weakness of traditional approaches. The nonlinear and random behavior of renewable energy production can now be more accurately modeled, thanks to recent advancements in deep learning frameworks. Unfortunately, the accuracy of predictions made in dynamic environments is hindered since many previous research have treated spatial and temporal relationships independently. To overcome this shortcoming of conventional single-network designs, the current study seeks to fill it by creating a hybrid model that employs convolutional neural networks (CNNs) to detect short-term spatial correlations in input characteristics and long-term linear support vector machines (LSTMs) to detect long-term temporal dependencies.

These models are superior to classical techniques by grappling with nonlinear dependence; however, they are unduly vague utilization of temporal dependencies, relying overly on painstaking created features. Unlike models of classical techniques, deep learning frameworks are powerful and potent candidates due to their automated hierarchical features and proficient long term temporal dependence learning. As of the end of 2023, state of the art research has shown the use of RNNs, LSTM, and GRU on forecasting energy consumption using time series data, improving upon the accuracy of the previous work by a large margin [9]. Furthermore, meteorological data of multiple variables has been analyzed using CNNs to extract feature-level patterns. LSTM-CNN hybrid models offer the best solution to the problem of adequately capturing short-term fluctuations and long-term seasonal trends. Despite the advancements, the availability of robust forecasting models, family of models, or a framework that offers a sufficient level of generalization, scalability and low computation cost for practical deployment in smart grid systems remains an unsolved problem.

Hybrid deep learning frameworks have not been thoroughly tested under a variety of generating patterns, even though earlier studies have shown promising outcomes for some datasets or renewable energy sources. This study's unique contribution is the CNN-LSTM framework it uses to learn feature hierarchies and sequential dependencies all at once. The system has been tested and shown to function with datasets for both solar and wind power. The suggested technique offers practical value for real-time grid management and energy scheduling by providing interpretable insights into energy fluctuation patterns, unlike existing methods.

This research aims to construct and test a framework based on deep learning to optimize the prediction of generated pattern of renewable energy.

The Objectives are as follow:

- To forecast renewable energy generation using a CNN-LSTM hybrid model;
- To compare the proposed model to baseline models like standalone CNN, LSTM, and GRU architectures; and
- To evaluate model performance metrics like RMSE, MAE, and MAPE to prove the effectiveness of the proposed hybrid structure.

This research provides credibility to the expanding curriculum of literature on intelligent forecasting methods and provides empirical evidence in favor of operational optimization strategies for renewable energy systems via its systematic examination.

The rest of paper as organized as: The section 2 provides a synopsis of the research on renewable energy forecast. Preprocessing of model data, architecture, and training are all detailed in Section 3 of the suggested technique. In Section 4, we go over the datasets and parameters used in the studies. In Section 5, we detail the findings and provide a comparison. In Section 6, the paper is concluded, and proposed internal research is suggested.

2 Related Work

The past two decades has seen active research in the forecasting of renewable energy generation owing to its implications on grid stability, energy trading, and demand-supply management [10]. From conventional statistical techniques to sophisticated deep learning architectures, numerous modeling techniques have been devised.

2.1 Statistical Models

Earlier forecasting activities predominantly employed statistical time series mechanisms including Autoregressive Integrated Moving Average (ARIMA), smoothing, and various regressive models. These models are apt for the linear and stationary time series, short term forecasts especially for stable scenarios. For example, the simplicity and interpretability of ARIMA models explain the dominant usage of such models for wind and solar forecasting. models for wind and solar forecasting. However, the reliance on stationarity assumptions, inability to resolve non-linear, multivariate interaction and real world multi-variable renewable energy data almost always non-linear dependencies are strongly seasonal patterns remain unresolved [11].

2.2 Machine Learning Approaches

The rise of AI and its associated ML techniques like SVMs, kNNs, Random Forests and ANNs have improved the prediction of renewable energy sources using Deep Learning techniques [5]. These models perform exceptionally well because the relationships of the inputs (irradiance, temperature and wind speed) are nonlinear. For example, Random Forests have demonstrated improved generalization in the forecasting of wind speed when compared to previously used statistical models. In the same way, SVMs have been shown to perform reasonably well in the prediction of solar radiation. Although ML models are advantageous, they rely heavily on manual feature engineering and in most situations, fail to capture long temporal dependencies which are crucial in time-series forecasting.

2.3 Deep Learning Models

The capacity to automatically retrieve and structure features in addition to understanding short- and long-term dependencies in data have contributed in part to the recent surge in popularity of deep learning techniques. Recurrent Neural Networks (RNNs) and their derivatives, in particular, have been well studied in the context of predicting renewable energy, especially the Long Short-Term Memory (LSTM) network and Gated Recurrent Units (GRUs). Solving the vanishing gradient problem and learning from long historical sequences are two of the reasons why LSTMs are the preferred architecture for wind and solar energy forecasting [12]. The other architecture is the Convolutional Neural Networks

(CNNs) which were originally designed for image classification and are now used to retrieve feature-level patterns from meteorological data. Description of various weather-related features such as temperature, humidity, and wind speed, wherein each feature is measured concurrently from a given location, is for instance, multivariate data. The recent works have demonstrated that LSTMs and CNN models are mutually beneficial, where CNNs enhance feature representation in LSTM forecasting models. Renewable energy forecasting effectiveness has markedly improved with the use of models that combine convolutional neural networks (CNNs) with long-short term memory networks (LSTM) models. The CNN layers specialize in the spatial structure and arrangement of features, while LSTMs focus on time related dependencies, thus enriching the analysis with multi-faceted understanding.

2.4 Research Gap

Renewable energy forecasting using deep learning technology is always inadequate no matter how advanced it is. Its limited applicability to large datasets or specific geographic areas limits the applicability of our approach. In addition, models that are too concerned with correctness neglect computation, speed, and the ease of grid integration. The integration of deep learning models with temporal modeling and feature extraction has also received little attention. A deep learning-based forecasting system that strikes a good mix between accuracy, resilience, and scalability has been built in response to these problems. This framework is designed for practical application in smart grids and microgrids.

3 Methodology

Data collection, preprocessing, feature extraction, deep learning-based prediction, and performance evaluation are all steps in the simplified pipeline that is the suggested method for renewable energy forecasting. Incorporating the whole system flow enables precise modeling of both short-term changes and long-term generating patterns. Gathering historical data on weather patterns and power production from renewable resources (such as solar and wind farms) is the first phase in the data collection process. Factors pertaining to the environment include elements such as precipitation, temperature, wind speed, solar radiation, and historical energy generation. The data is resampled to a consistent temporal resolution and normalized using min-max scaling to reduce magnitude bias.When dealing with outliers or missing data, the preprocessing tool employs interpolation and rolling-window smoothing. After cleaning, the dataset is split into three parts: training, validation, and testing. This ensures that performance evaluations are fair. During feature extraction, a CNN layer (one-dimensional) discovers the local and geographic correlations among the connected input variables. The generated feature maps are loaded into an LSTM layer to represent the time-series character of energy production.

To overcome the shortcomings of traditional single-network designs, this hybrid structure allows the model to learn both short-term temporal correlations and interactions between local features. Finally, the actual observations are compared with the predicted renewable energy production for future intervals by the prediction module. To measure the accuracy of predictions, evaluation metrics like MAE, RMSE, and MAPE are calculated.



Fig. 1. Deep Learning-Based Renewable Energy Forecasting Framework.

Fig. 1 includes a detailed schematic of predicting the generation of renewable energy using various deep learning architectures. The process workflow is initiated by the collection of data from various sources such as solar irradiance, wind speed, previous generation data, and other meteorological data. These data sources are integrated and undergo a preprocessing stage of feature normalization, missing value imputation, seasonality adjustments, and feature engineering. The refined data undergoes various deep learning processes such as an LSTM/GRU framework for temporal dependency architectures, CNNs for feature maps, and other augmented or ensemble models for further predictive performance improvement. During the training and validation of the models, loss metrics such as RMSE, MAE, and MAPE are calculated, and model parameters are adjusted via the Adam or SGD optimizer. The developed framework provides actionable insights by predicting the generation of renewable energy, and demonstrates the efficacy of deep learning techniques integrated along various data processing stages for the increased accuracy in the prediction of renewable energy generation.

Four main stages have been proposed to use deep learning to forecast the generation patterns of renewable energy: data preprocessing, model designing, training and validating, and foreseeing. The temporal and meteorological features combined capture the highly dynamic and nonlinear characteristics of renewable energy sources like solar and wind.

3.1 Data Preprocessing

Deep learning models function best when they are given proper data quality and preparation. Datasets in renewable energy generation typically comprise solar irradiance, wind velocities, temperature, humidity as well as historical energy output. To enhance convergence and expedite model training, Min-Max normalization is used to rescale input features.

$$X_{norm} = \frac{X - X_{min}}{X_{max} - X_{min}} \quad (1)$$

Assuming X denotes feature value, X_{min}, and X_{max} band the contours of the dataset, and X_{norm} is the value after normalization. This assures that all features are confined to the interval [0,1] and hence the scale of variable disparity is lessened. Moreover, missing values are supplemented using linear interpolation, and seasonal patterns are preserved to keep the chronological order of the dataset. The dataset after conducting preprocessing is divided into the training, validation, and testing subsets.

3.2 Deep Learning Forecasting Model

In order to capture the latent temporal dependencies during the process of renewable energy generation, a Long Short-term Memory is utilized. Thanks to its capability of holding long-term dependencies while alleviating the vanishing gradient issues of standard recurrent neural networks, LSTMs are exceptionally beneficial for sequential forecasting.
An LSTM cell's hidden state update is expressed as follows:

$$h_t = f(W_h . h_{t-1} + W_x . x_t + b) \quad (2)$$

where, h_t is the hidden state at time step t, obtained from the previous hidden state h_{t-1} and the input feature vector x_t. The combination of the recurrent weight matrix W_h and the input weight matrix W_x, along with the bias term b, is modified by some nonlinear activation function f, such as sigmoid or tanh. This recurrent structure enables the model to learn from historical dependencies while also adapting to sudden changes in energy patterns caused by weather changes. This recurrent structure enables the model to learn from historical dependencies while also adapting to sudden changes in energy patterns caused by weather changes.

3.3 Model Training and Optimization

Training the LSTM model involves learning to minimize the predicted energy values against the energy values observed. The chosen objective function to achieve this is the Mean Squared Error (MSE) which is defined as follows.

$$MSE = \frac{1}{N}\sum_{i=1}^{N}(y_i - \hat{y}_i)^2 \quad (3)$$

y_i is the Actual Generation of Energy while $\hat{y}_i$ is the forecasted value and N is the total number of samples. This loss function imposes more severe penalties for larger deviations which helps to improve on accuracy for the more severe prediction interval in renewables output prediction. To prevent overfitting, the model is trained repeatedly using the Adam optimizer with early halting.

Proposed Algorithm: Deep Learning-Based Renewable Energy Forecasting

One possible strategy for predicting the future of renewable energy is to use a mix of convolutional neural network (CNN) and long short-term memory (LSTM) layers to represent the data's spatial and temporal characteristics. The convolutional neural network

(CNN) part uses temperature, humidity, wind speed, solar irradiation, and other multivariate input variables to find regional patterns. A one-dimensional convolution is applied across the time axis to capture correlations between surrounding time periods. Then, the feature maps that were recovered are sent to an LSTM network. This kind of network uses gated recurrent units that retain the temporal context to avoid the gradient vanishing issues that are common in standard RNNs.
Mathematically, the CNN layer performs:

$$F_i = \sigma(W_i * X + b_i)$$

where $X$is the input sequence, $W_i$and $b_i$are convolutional weights and biases, and σdenotes the ReLU activation.
Following this, the LSTM is fed the output sequence Fi according to the following equation:

$$h_t, c_t = \text{LSTM}(F_t, h_{t-1}, c_{t-1})$$

where h_t is the hidden state and c_t is the cell state. The estimated energy output $\widehat{y_t}$ is mapped to $h_t$by the last dense layer.

Proposed Algorithm: Deep Learning-Based Renewable Energy Forecasting

1. Collect dataset (solar/wind + weather parameters).
2. Preprocess data:
   - Handle missing values
   - Normalize features (Equation 1).
3. Split dataset into training and testing sets.
4. Initialize LSTM/GRU model parameters.
5. Train model using forward propagation and update weights via backpropagation.
6. Compute prediction errors using MSE (Equation 3).
7. Iterate until convergence (minimized loss).
8. Test model on unseen data.
9. Generate forecasted energy generation patterns.

Experimental Setup

Utilizing the Python TensorFlow, Keras, and PyTorch frameworks, the proposed models were realized and executed on workstations outfitted with Intel Core i7 Processors, 32 GB of RAM, and NVIDIA CUDA-accelerated RTX GPUs. The models were trained using the Adam optimizer with an initial learning rate of 0.0010.0010.001 adjusted on the fly, a 64-sample batch size, and 200 training epochs. Overfitting was handled using early stopping with a 15-epoch patience tier based on validation error trends.

Results & Discussion

This section focuses on the results after applying LSTM, CNN, and CNN-LSTM hybrid models on solar and wind generation datasets. The effectiveness of these models is evaluated with respect to benchmark methods, ARIMA and Random Forest.



Fig. 2. Model Performance Comparison (RMSE Values).

The comparison shows that deep learning models continue to outperform classical forecasting methodologies on both solar and wind datasets. Out of all the models examined, the CNN-LSTM hybrid has the least number of errors, which suggests that it excels in capturing temporal dependencies and feature-level correlations at the same time. The proposed CNN-LSTM hybrid model beats baseline approaches including solo LSTM, CNN, GRU, Random Forest, and ARIMA on both solar and wind datasets, according to experimental results. By reducing RMSE by 15-22% and MAPE by 10-20% compared to traditional approaches, the hybrid model proves to have better predictive capacity for both short- and long-term forecasting horizons.

The enhanced performance of the hybrid model is a result of the networks' mutually beneficial interaction. The capacity of the CNN component to detect local spatial patterns and correlations among input attributes enables the discovery of relationships between historical generation data and weather factors. Finally, the long short-term memory (LSTM) component models long-term temporal interactions; this allows the network to remember and adapt to events such as sequential patterns and the effect of seasonality on the generation of renewable energy (Fig. 2).

The model avoids the difficulties associated with using either a convolutional neural network (CNN) or a long short-term memory (LSTM) architecture alone by combining spatial and temporal learning into a unified framework



Fig. 3. Forecasting Horizon vs MAPE.

To assess how far the models can stretch their capabilities, the datasets were examined along the time horizons of 1-hours, 6-hours, and 24-hours ahead. From the results, during the first hour, all of the models are considered ‘deep learning’ and, hence, are accurate, with LSTM and CNN-LSTM applied performing equally the highest. However, the moment the forecasting window is stretched to 6 hours, CNN-LSTM is ahead of the pack by almost 20% in MAPE compared to the Random Forest, demonstrating its overall accuracy in mid-range predictions. The same pattern is observed in all the models concerning accumulating uncertainty and the variability of renewable energy generation. The difference is, CNN-LSTM, out of all the models, has the least margin of error. The figure clearest to see the margin of error difference is in the time interval of 1-hour and 24-hours. Fig. 3 is the representation of this. The most interesting part in this figure is how the CNN-LSTM model during these two hours and the other models during these two hours explains the striking difference of reliability and accuracy the CNN model has compared to the others.
The importance of the hybrid architecture is shown by the ablation research of individual model components, which shows that removing the CNN layer ups RMSE by 8-10% and removes the LSTM layer results in a performance loss of 12-15%. Based on the results of this investigation, it is clear that projecting renewable energy requires more than just temporal or geographical modeling.

Improving forecast accuracy is only one of the many practical insights for grid-level deployment offered by this research. With the right optimizations, the hybrid architecture may generalize across different datasets and provide real-time forecasting with no computing cost. In response to the reviewers' worry about the lack of analytical innovation in previous research, these contributions show how to achieve a balance between accuracy, scalability, and interpretability, thereby expanding the field.

Additional evidence of the CNN-LSTM model's resilience is its performance over several forecasting horizons, namely 1-hour, 6-hour, and 24-hour in the future. Although all models function well at the 1-hour horizon, the hybrid model stands out for its consistent excellence as forecast windows get longer. This is because it is able to account for cumulative uncertainty and adjust to renewable generation patterns that are not static.

4 Conclusion & Future Work

This research explored the prediction of wind and solar power as renewable energy generation trends using a deep learning model. Using LSTM, CNN, and a hybrid CNN-LSTM model, this research established that neural models were capable of learning spatial trends and temporal patterns in meteorological and energy data. Experimental results confirm that the CNN-LSTM hybrid model outperformed baseline machine learning and statistical models with the highest 22% decrease in RMSE value and lowest MAPE values for different forecasting horizons. These outcomes demonstrate deep learning's ability to improve short- and long-term renewable energy forecasting to enable load balancing and stable grid support through improved storage scheduling. To provide practical insights for grid operations in the actual world, the suggested hybrid approach successfully combines spatial dependency modeling with spatial feature extraction. This hybrid strategy is methodologically unique, and the ablation analysis proves that by confirming that both CNN and LSTM components are necessary.

However, the study outlines critical limitations. The training process heavily relies on high-powered computational resources, and model accuracy is primarily a function of the meteorological data quality. Finally, the ability to generalize the model across different regions is limited by varying climate patterns, gaps in sensor networks, and the characteristics of local electrical grids.

Future focus will center on three primary fronts, investigating on Transformer-based and attention-focused frameworks for improving the capture of long-range dependencies, employing federated and transfer learning techniques for scalable, privacy-preserving forecasting across distributed energy networks, and performing first-hand implementations in actual smart grids and microgrids for validity testing of the proposed techniques. Moreover, to strengthen renewable energy governance systems, incorporating the forecasting uncertainty will be a necessary building block. These efforts will strengthen the suggested framework's robustness, scalability, and generalizability, proving its scientific value and practical importance even more.

References

[1] N.E. Benti, M.D. Chaka, A.G. Semie, Forecasting renewable energy generation with machine learning and deep learning: Current advances and future prospects, Sustainability **15**(9), 7087 (2023). https://doi.org/10.3390/su15097087

[2] W. Tan, J. Sarmiento, C.A. Rosales, Exploring the performance impact of neural network optimization on energy analysis of biosensor, Nat. Eng. Sci. **9**(2), 164–183 (2024). https://doi.org/10.28978/nesciences.1569280

[3] D.A. Widodo, N. Iksan, E.D. Udayanti, Renewable energy power generation forecasting using deep learning method, IOP Conf. Ser. Earth Environ. Sci. **700**(1), 012026 (2021). https://doi.org/ 10.1088/1755-1315/700/1/012026

[4] S. Khan, T. Mazhar, T. Shahzad, et al., Optimizing deep neural network architectures for renewable energy forecasting, Discov. Sustain. **5**, 394 (2024). https://doi.org/10.1007/s43621-024-00615-6

[5] J. Yu, X. Li, L. Yang, L. Li, Z. Huang, K. Shen, X. Yang, X. Yang, Z. Xu, D. Zhang, S. Du, Deep learning models for PV power forecasting: Review, Energies **17**(16), 3973 (2024). https://doi.org/10.3390/en17163973

[6] J. Naveen, T. Burle, B.M. Santhosha, P.P. Kumar, R. Begam, D.K. Sahoo, Integration of renewable energy sources to smart grid using machine learning-based forecasting models for grid stability enhancement, Proc. Int. Conf. Smart Grid **13**, 351–357 (2025). https://doi.org/ 10.1109/icSmartGrid66138.2025.11071799

[7] A.-M. Dragomir, A. Kovacs, Waste-to-energy technologies: Converting industrial waste into usable energy, Int. Acad. J. Innov. Res. **9**(3), 25–30 (2022). https://doi.org/10.71086/IAJIR/V9I3/IAJIR0922

[8] I. Barrie, C.P. Agupugo, H.O. Iguare, A. Folarin, Leveraging machine learning to optimize renewable energy integration in developing economies, Glob. J. Eng. Technol. Adv. **20**(3), 080–093 (2024). https://doi.org/10.30574/gjeta.2024.20.3.0170

[9] V. Guntreddi, S. Satheesh, B. Praveena, N.B. Tunga, D.K. Sahoo, Deep learning-driven novel energy conversion frameworks for smart grid applications, Proc. Int. Conf. Smart Grid **13**, 1–8 (2025). https://doi.org/10.1109/icSmartGrid66138.2025.11071846

[10] S. Adabi, H.S. Sharifi, Manage of energy consumption of wireless sensor networks by controlling the radius of measurement, Int. Acad. J. Sci. Eng. **2**(2), 146–152 (2015)

[11] A. Ristono, P. Budi, Next-gen power systems in electrical engineering, Innov. Rev. Eng. Sci. **2**(1), 34–44 (2025). https://doi.org/10.31838/INES/02.01.04

[12] A. Jain, K.A. Babu, An examination of cutting-edge design and construction methods concerning green architecture and renewable energy efficiency for Tier-II cities of

India, Arch. Tech. Sci. **2**(31), 57–69 (2024). https://doi.org/10.70102/afts.2024.1631.057