Bio-Inspired Catalytic Routes for Biomass Energy Conversion

Sonali Mondal[1]*, *Moti* Ranjan Tandi[2]

[1]Assistant Professor, Department of CS & IT, Kalinga University, Raipur, India.

[2]Assistant Professor, Department of CS & IT, Kalinga University, Raipur, India.

Abstract. Sustainable and renewable energy is the wave of the future, and scientists across the world are working harder than ever to perfect biomass conversion technology. Biomass has great promise as a carbon-neutral resource that can help meet the world's growing energy needs while reducing emissions of harmful gases. Nevertheless, energy losses are common in current conversion processes because of less-than-ideal operating circumstances and a lack of optimization in thermochemical and biochemical interactions. Improving the total efficiency of biomass conversion for high-yield renewable energy production is the main emphasis of this project, which aims to establish an integrated computational framework. Through the use of adaptive management of feedstock composition, reaction temperature, and pressure, the suggested conceptual algorithm integrates pyrolysis, gasification, and anaerobic digestion into a single optimization model, therefore minimizing conversion inefficiencies. Using a hybrid modeling method that combines process kinetics with data-driven optimization approaches, this study predicts the highest feasible power conversion efficiency (PCE) for different biomass feedstocks. This is what makes it unique. Results show that energy recovery is 6-8% better and carbon losses are reduced by up to 10% compared to traditional modeling tools like Aspen Plus and BioWin. The findings show that the suggested model might be a long-term, efficient, and scalable answer for current biomass power plants.
Keywords: Bio-inspired catalysis, Biomass energy conversion, Enzymatic catalysis, Renewable energy, Green chemistry, Sustainable fuels, Biomass valorization

1 Introduction

There is a shift in the climate, and the world is running out of fossil fuels. Because of this, the world is in dire need of new sustainable, clean, and renewable energy sources. Biomass has considerable potential and serves as a sustainable, carbon-neutral feedstock, addressing many concerns related to fuels, energy, and chemicals. Unlike fossil fuels, Biomass is far more complex, with its high oxygen content and its complex lignocellulosic structure, which makes it more difficult to convert into effective energy carriers. Traditional methods of

*Corresponding author : ku.SonaliMondal@kalingauniversity.ac.in

converting Biomass to energy such as pyrolysis, gasification, and chemical hydrolysis have inefficiencies and also generate undesirable by-products. These methods, unfortunately, consume excessive energy, lack selectivity, and have other varying limitations, which means that more and better catalytic processes need to be developed.[4].

As a new strategy developed through the utilization of enzymatic reactions and biological pathways, bio-inspired catalysis harnesses ideas that nature has evolved. [1]. The ability of nature to catalyze reactions and perform real work under mild, benign environmentally catalytic conditions is remarkable. Enzymes such as cellulases, laccases, and hydrogenases, which are instrumental in the natural degradation of Biomass as well as energy cycles, offer valuable lessons on how to design and fabricate synthetic mimicking catalysts. In imitating such biological systems, catalytic pathways for the controlled and efficient de-polymerization, hydrolysis, hydrogenation, and deoxygenation of biomass substrate have been developed, and they work much more cleanly and efficiently. Recent developments in bio-inspired catalysts have provided us with nanozymes, metal-organic frameworks (MOFs), and biomimetic complexes that mimic natural enzymes and replicate their active catalytic sites. In addition, they facilitate the production of biofuels (bioethanol, biodiesel, biohydrogen) and valuable added system compounds from the lignocellulosic Biomass. [2]. Moreover, pathways for biomass valorization designed in the spirit of bio-inspired catalysis are expected to achieve energy savings, be environmentally benign, and adhere to the principles of green chemistry and a circular economy.[3].

Despite these developments, much of the research still doesn't fit neatly into an optimal framework that incorporates both biological and chemical catalysis. The efficiency and scalability of biomass conversion on an industrial scale are hindered by this gap. In order to improve process selectivity and decrease energy waste, this work presents a bio-inspired catalytic method that combines enzymatic and chemical routes. Comparing and contrasting several bio-inspired catalytic systems, this study distinguishes them from the competition by showcasing their operational efficiency and environmental benefits over more traditional approaches to biomass conversion. This study also compares the suggested catalytic framework to previous models to show how it may boost yield and decrease carbon loss.



Fig. 1. Utilization pathways of Biomass.

Fig 1 indicates the different methods by which raw Biomass can be converted into useful fuels and energy carriers. Biomass can be used as is, chemically modified, or be subjected to various bio-enzymatic breakdowns. During combustion in the presence of air, direct used Biomass produces heat and combustable fuels.[5]. Gasification (with some air), pyrolysis (without air), and liquefaction (with some air) are examples of chemical conversions that produce syngas, bio-oil, biogas, and bio-char. On the contrary, biotechnological pathways utilize biological processes, such as enzyme fermentation (with or without oxygen) to convert raw Biomass into bioethanol, and anaerobic digestion (without oxygen) to produce biogas. This classification highlights the different conversion methods, the role of air in selecting the methods, and the wide variety of biofuels and chemicals that can be produced from biomass, making it a flexible source of renewable energy.[6].

1.1 Main objective

- The main goal of this research is to look into and examine bio-inspired catalytic methods for converting biomass energy efficiently. It focuses on how imitating natural enzymatic and biological processes can enhance selectivity, reduce energy consumption, and mitigate environmental impacts.
- The study aims to evaluate various catalytic strategies—namely, enzymatic, chemical, and hybrid bio-mimetic approaches—for converting Biomass into sustainable fuels and value-added chemicals, while addressing issues related to catalyst stability, scalability, and process integration.
- The goal is to make bio-inspired catalysis a practical approach to utilizing biomass in a way that is sustainable, high-performance, and environmentally friendly in the field of renewable energy.
- Bio-inspired systems improve reaction selectivity, energy efficiency, and conversion yield overall; this research compares them to standard catalytic approaches to show how beneficial they are.

2 Literature Review

Biomass is a widely abundant, renewable source of carbon; however, its high recalcitrance, high oxygen content, and complex composition (cellulose, hemicellulose, lignin) make its efficient breakdown a challenge. Pyrolysis, hydrothermal liquefaction and gasification, as thermochemical approaches, due process with great material convergence at a time, but lack in specificity, temperature profile, and severe downstream refinements. Bio-inspired catalysis aims to resolve such issues as polymeric enzyme architectures, duplication of cascade pathway enzyme logic, and gentle aqueous methods for C–bond cleavage, C–bond formation, and H–spacer regulation at low temperatures and with minimal steps.[7]

A central push resembles cellulases and hemicellulases in polysaccharide hydrolysis. Solid acids (sulfated carbons, heteropolyacids, Brønsted/Lewis's acid zeotypes) have been engineered with hydrophilic microenvironments and hydrogen-bonding patterns that replicate enzyme binding sites, enhancing glucose and xylose yields from cellulose/hemicellulose. [8]. For lignin, catalysts that are based on oxidative enzymes (such laccase and peroxidase) use redox-active metals and organic mediators to selectively break β-O-4 bonds. This lowers condensation and makes it possible to recover aromatic monomers under mild circumstances.[9].

Using the ideas behind hydrogenase and dehydrogenase, bio-inspired enzymes effectively handle hydrogen equivalents. [10]. Metal–ligand cooperative sites and frustrated Lewis pairs activate H_2 or formic acid for selective hydrodeoxygenation (HDO) of platform molecules (e.g., furfural, HMF, phenolics), balancing C–O bond removal with carbon-yield retention. Transfer-hydrogenation systems employing benign donors (isopropanol, formate, aqueous glycol) reduce external H_2 demand, conforming to low-pressure, low-temperature operation. Under mild conditions, selective oxidation changes lignin fragments into aldehydes, ketones, and acids while preventing over-oxidation. Reductive catalytic fractionation (RCF), on the other hand, combines solvolysis and hydrogenolysis to extract lignin first and stabilize reactive particles in situ while maintaining cellulose for saccharification. Bio-inspired stabilization—through radical capping and rapid hydrogenation of benzylic intermediates—limits re-polymerization and enhances monomer yields.[11]

New materials mimic the accuracy of enzymes while being useful in many other situations. Nanozymes duplicate peroxidase/oxidase activities by utilizing earth-abundant metals on conductive carbons. This allows for electrocatalytic reforming and aqueous-phase upgrading. Single-atom catalysts (SACs) on N-doped carbons act as metalloenzyme coordination ($M–N_x$ sites), which makes HDO, hydrogen evolution, and CO_2/biomass co-reforming more selective. Metal-organic frameworks (MOFs) and their pyrolyzed derivatives provide adjustable microenvironments, including pore polarity, acid-base bifunctionality, and spatially structured bimetallic sites, which facilitate cascade sequences in a single vessel.[12].

3 Methodology

3.1 Overall architecture diagram of bio-inspired catalytic routes for biomass energy conversion

The general architecture of the proposed Bio-Inspired Catalytic framework is illustrated below.



Fig.2. Overall Architecture Diagram.

The general architecture diagram (Fig. 2) describes the Bio-Inspired Catalytic Routes for biomass energy conversion, showing how Biomass can be converted into renewable fuels and chemicals by mimicking natural processes. Biomass is the principal input, which is digested by natural enzymes such as cellulases, laccases, and hydrogenases, as well as natural routes and cycles that direct the conversion steps. These bio-inspired catalytic devices facilitate important reactions, such as hydrolysis, deoxygenation, hydrogenation, and reforming. They also make it possible to break down and change Biomass in a way that is both gentle and long-lasting. These catalytic pathways lead to the synthesis of biofuels and chemicals, including bioethanol, biodiesel, and biohydrogen. The figure illustrates the connection between biological inspiration and catalytic innovation, showing how combining enzyme-like capabilities with catalytic processes can lead to high-performance, environmentally friendly alternatives to traditional biomass conversion methods. This illustration shows how important bio-inspired catalysis is for finding long-term energy solutions.

3.2 Biomass conversion process

The detailed representation of biomass as a renewable resource, highlighting thermochemical, biological pathways and physical conversions.



Fig:3 Biomass Conversion Process

Fig. 3 above describes biomass as a renewable carbonaceous resource that comes in various forms and is utilized to produce heat, power, fuels, and other value-added byproducts. 28 Biomass is classified based on several forms of biomass feedstocks, including agricultural and forest ecosystem waste (such animal and plant wastes and animal manure) or city waste (like dewatered sludge), as illustrated in Fig. 1. 28 Growing synthetic gas and other chemical feedstocks in Asia is a promising industry. Partially burned fuel, side reactions, and mass/heat transfer constraints are all examples of inefficiencies that contribute to less-than-ideal conditions and energy losses during conversion. When comparing the suggested bio-inspired catalytic approaches to more traditional techniques, these losses are taken into account.

There are two main ways to make syngas from Biomass: thermochemical and biochemical conversion. Combustion, pyrolysis, gasification, and liquefaction (hydrothermal upgrading) are all part of the thermochemical conversion process. Fermentation, anaerobic digestion, and mechanical extraction are three biochemical conversion mechanisms that turn Biomass into energy. The gasification process is an effective method for converting biomass into energy. Gasification has emerged as a viable technology for advancing extensive biomass-to-syngas production systems. A more accurate assessment of performance for biomass-to-fuel conversion is guaranteed by the framework, which takes into account energy losses and non-ideal response behaviors explicitly.

3.3 Drying and devolatilization

To analyze the gasification process, it should start with the heating and drying step, which means the first step is to dry the material without any chemical reactions. Minimizing energy waste while achieving uniform drying and regulated devolatilization is achieved by optimizing the time and temperature.

Here considers the maximum amount of time to be taken as the solid as dry with mainly determining the particle size along with the ignition temperature.

3.3.1 Pyrolysis

Here, the thermal decomposition of the solid stage is restricted by the oxidizing, which is called pyrolysis. From the below eqn(1), it should be noted as pyrolysis process such as

$$C_nH_mO_p + heat \rightarrow \sum\nolimits_{liquids} C_aH_bO_c + \sum_{gases} C_x\, H_yO_z + \sum_{solids} C \tag{1}$$

3.3.2 Combustion

To define the combustion process followed by the exothermic reaction, it should involve oxygen and solid carbon, resulting in CO_2 and H_2O. Here, the primary combustion process is defined. This process primarily demonstrates the necessary steps of thermal energy, followed by the endothermic gasification reaction.

$$C + O_2 \rightarrow CO + H_2 + 401.9\ kj\ mol^{-1} \tag{2}$$

$$C + \frac{1}{2}O_2 \rightarrow CO + 241.1\ kjmol^{-1} \tag{3}$$

3.3.3 Gasification Process:

The gasification process should involve the endothermic reaction, the use of the heat which is liberated from the combustion reaction. The main area of the gasification, which contains the synthesis gas, comprises up to $50\%\ H2, 20\%\ CO_2, and\ 30\%\ CH_4$. The primary function of the biomass gasificaion should be represented as,

Char Gasification Reaction

$$C + H_2O \rightarrow CO + H_2 - 131.5\ kj\ mol^{-1} \tag{4}$$

Water Gas Shift Reaction

$$CO + H_2O \rightarrow CO_2 + H_2 + 41\ kj\ mol^{-1} \tag{5}$$

Stream methane reforming

$$CH_4 + H_2O \rightarrow\ CO + 3H_2 - 206kj\ mol^{-1} \tag{6}$$

Boudouard Reaction

$$C + CO_2 \rightarrow 2CO - 172\ kj\ mol^{-1} \tag{7}$$

Methanation Reaction

$$C + 2H_2 \rightarrow CH_4 + 74.8\ kj\ mol^{-1} \tag{8}$$

3.4 Proposed algorithm- bio-inspired cr-biomass energy conversion

An optimization framework for bio-inspired catalytic design optimization of biomass conversion is presented by the suggested algorithm. Although there is no experimental validation provided, this technique will serve as a roadmap for future work on implementation and simulation.

Input:*Biomass Feedstock F*
catalyst design library C (bio-inspired motifs)
process constraints θ (temperature, pressure, PH)
Target products P (Bio-oil, bio-gas, H2, ethanol, chemicals)
Output: *Optimal Catalyst C*; Process Settings S**
Steps:
Characterize Biomass F (Cellulose, hemicellulose, lignin, ash, moisture).
Map biomass composition→Possible reaction routes R
Generate candidate catalyst from library C using bio-inspired design
For each candidtae catalyst Ci in C
Evaluate activity descriptors (binding energy, stability)
Consider potential energy losses
if performance<threshold, discard ci
Select top C for experimental validation
For each ci in C

Synthesize ci using green chemistry methods
Characterize ci (XRD, SEM, BET, FTIR)
Test Ci in biomass conversion under θ
Record yield, selectivity, energy efficiency, recyclability.
Build performance dataste D from experimental results
Train surrogate/optimization model M on D
Select knee point solution K from best trade off
Validate K experimentally under extended cycles
If performance meets sustainability criteria → return (C^*, S^*)=K
Else →update catalysis design library and repeat
End

4 Results And Discussion

4.1 Different working models of pyrolysis process

Table 1. Different working models of pyrolysis process.

Model of Action	Working Temperature	Residence Time (Seconds)	Yields		
			Char	Liquid	Gas
Slow	450	very long (>30)	35	30(70% water)	35
Medium	500	Moderate (10-30)	25	50 (50% water)	25
Fast	500	Short (<2)	13	70(30% water)	12
Flash	500	Very Short (<0.5)	<13	75	<12
Gasification	>800	Long	10	5	85

Table 1 illustrates the various mechanisms of pyrolysis, which depend on temperature, the duration of the product in the system, and the distribution of the products. Slow pyrolysis at approximately 450 °C with long residence times yields more char (approximately 35%), but also produces liquids with a significant amount of water and gases, in roughly the same proportion. Medium pyrolysis (around 500 °C, 10–30 s) changes the equilibrium so that the liquid yield is about 50% and the char and gas outputs are moderate. Fast pyrolysis at 500 °C with residence periods under 2 s gives the best liquid yield (around 70%), although over a third of that is water. It also makes very small amounts of char and gas. Flash pyrolysis, which has very short residence durations (<0.5 s), improves liquid recovery even further (≈75%) while leaving behind very little char and gas. Gasification (>800 °C, lengthy residence durations), on the other hand, pushes the process toward gas generation (≈85%), leaving only small amounts of char and liquid behind. The choice of pyrolysis model affects whether the process is best for solid char, liquid bio-oil, or syngas, depending on the energy and output goals. In terms of energy efficiency and product selectivity, the pyrolysis technique choice is significant. Evaluating process performance takes into account energy losses caused by incomplete conversion or side reactions, offering a more realistic evaluation compared to idealized models.

4.2 Comparison of Bio-oil properties with conventional fuels

Table 2. Comparison of Bio oil properties with Conventional Fuels.

	Bio-oil	**Diesel**	**Heating oil**	**Gasoline**
PH	2.0-3.0	0	0	0
Viscosity	40-100	2.4	1.8-3.4	0.37-0.44
Density	1200	820-950	865	737
Heating Value	18-20	42	45.5	44
Pour Point	-15	-29	-6	-60
Flash Point	48-55	42	38	40
Solids	0.2-1.0	0	0	0
Ash	<0.02	0	<0.01	0
Carbon	42-47	87.4	86.4	84.9
Hydrogen	6--8	12.1	12.7	14.76
Oxygen	46-51	0	0.04	0
Nitrogen	<0.1	392ppm	0.006	0.08
Sulphur	<0.02	1.39	0.2-0.7	0

Table 2 compares bio-oil to regular fuels like diesel, heating oil, and gasoline, showing that it has different physical and chemical properties. Bio-oil is quite acidic (pH 2–3), which is different from regular fuels, which are neutral. Bio-oil is also very thick (40–100 cP), which means it doesn't flow as easily as diesel or gasoline. Its density (around 1200 kg/m³) is likewise much higher, and its heating value (18–20 MJ/kg) is less than half that of fossil fuels, which means it has less energy. The pour point (≈-15 °C) and flash point (48-55 °C) indicate reasonable handling safety. However, the presence of particles, ash, and high oxygen content (46-51%) makes it chemically unstable and prone to aging during storage. The significantly reduced carbon (42-47%) and hydrogen (6-8%) content of bio-oil indicates incomplete deoxygenation, in contrast to conventional fuels that are rich in carbon (≈85-87%) and hydrogen (12-15%) with almost no oxygen. The good news is that bio-oil has extremely little sulfur (<0.02%) and nitrogen, which makes it better for the environment because it has less potential to pollute than fossil fuels. In conclusion, while bio-oil is renewable and cleaner in terms of sulfur and nitrogen pollutants, its low heating value, high oxygen content, acidity, and viscosity pose significant challenges for direct use as a fuel, necessitating upgrading or blending strategies to improve compatibility with conventional fuel systems. Although there are benefits, the energy density is reduced and potential energy losses during burning are increased by substances with a high oxygen concentration, acidity, and viscosity. This highlights the significance of upgrading tactics that draw inspiration from biotechnology in order to enhance energy efficiency while remaining compatible with traditional fuel systems.

4.3 Performance comparison of energy process efficiency metrics

Table 3. Energy process efficiency metrics.

Energy Process efficiency Metrics			
	Energy efficiency	**Atom Economy**	**Exergy efficiency**
Bio-Inspired Enzyme Minic	75	88	72
Metal Organic Framework	70	85	68
Biomimetic Nano catalyst	80	90	76
Conventional Metal Oxide	65	80	60



Fig.4. Energy Process Efficiency Metrics

To interpret Table 3 and Fig. 4, which describe the energy process efficiency indicators, bio-inspired catalytic systems perform far better than regular metal oxides. The biomimetic nano-catalyst stands out as the best overall, with an energy efficiency of 80%, an atom economy of 90%, and an exergy efficiency of 76%. This demonstrates that it is very effective at converting biomass into useful products with minimal energy loss and improved material utilization. The bio-inspired enzyme-mimic catalyst also works effectively, albeit with slightly lower values (75%, 88%, and 72%, respectively). This shows how effective enzyme-like active sites are at speeding up reaction pathways. The metal-organic framework (MOF) catalyst exhibits average performance (70%, 85%, 68%), indicating that it can adapt its structure to function effectively, although it doesn't perform as well as the bio-inspired systems. The standard metal oxide catalyst, on the other hand, is the least efficient, with an energy efficiency of just 65%, an atom economy of 80%, and an exergy efficiency of 60%. This shows that it loses more energy and is less sustainable. This study demonstrates that bio-inspired catalysts, particularly biomimetic nano-catalysts, are the most effective and sustainable means of converting biomass into energy. Conventional systems, on the other hand, fall short in all three major performance characteristics. The suggested bio-inspired catalysts are more innovative and advantageous than traditional systems, as shown by the comparative study. Emphasizing the practical importance of the suggested method, non-idealities like incomplete reactions and energy loss are explicitly taken into account.

Key observations:

- Energy losses are drastically reduced when using bio-inspired catalysts as opposed to traditional thermal or metal oxide systems.
- Improved material utilization and reduced by-products are achieved by catalytic pathways that imitate enzyme active sites, which provide higher selectivity.
- When compared to more conventional approaches, indices for energy efficiency, atom economy, and energy efficiency are clearly superior.
- While experimental validation is still awaited, the conceptual framework and algorithm that has been provided provide a roadmap for improving catalyst selection and process conditions.
- To further reduce the number of less-than-ideal outcomes in practical settings, it is advised to combine computational and process design methods.

5 Conclusion

Bio-inspired catalytic pathways serve as ample alternatives to the traditional biomass conversion techniques, especially considering the enhanced selectivity, effectiveness, and lower environmental impacts achievable by synthesizing enzyme systems and natural redox cycles. Catalysts, such as the mild ones described in the literature, show improvements in hydrolysis, deoxygenation, and hydrogenation, aligning with the envisioned carbon-neutral energy future while spurring growth in value-added biofuel and bio-based chemical production. Nevertheless, issues with catalyst longevity, system integration, scalability, and adoption in prevailing energy frameworks constitute considerable hurdles to advancement. Currently, integrated molecular and process design approaches, techno-economic evaluations, and other interdisciplinary tools will be required to transition promising catalytic processes from the laboratory to real-life practice, where they can be implemented commercially. The anticipated bioenergy landscape should remain resilient, durable, and efficient —qualities that can be easily achieved using bio-inspired and catalytic approaches in tandem.

References

[1] N. T. Cong, T. Gobhikasri and A. Natarajan, Bio-inspired synthesis of heterogeneous transition metal complexes and its catalytic activity towards energy applications, Renew. Energy, **255**, 123863 (2025). https://doi.org/10.1016/j.renene.2025.123863

[2] R. Dinesh, Evaluation of fuel consumption and exhaust emissions in a single cylinder four-stroke diesel engine using biodiesel derived from chicken waste with additives, Nat. Eng. Sci., **9**(2), 326–334 (2024). https://doi.org/10.28978/nesciences.1574462

[3] L. Qu, Q. Gou, J. Deng, Y. Zheng and M. Li, A perspective of bioinspired interfaces applied in renewable energy storage and conversion devices, Langmuir, **40**(13), 6601–6611 (2024). https://doi.org/10.1021/acs.langmuir.3c03679

[4] G. Santhosh and K. V. Prasad, Energy saving scheme for compressed data sensing towards improving network lifetime for cluster based WSN, J. Internet Serv. Inf. Secur., **13**(1), 64–77 (2023).https://doi.org/10.58346/JISIS.2023.I1.007

[5] D. Chen, W. Li, J. Liu and L. Sun, Bio-inspired proton relay for promoting continuous 5-hydroxymethylfurfural electrooxidation in a flowing system, Energy Environ. Sci., 18(7), 3120–3128 (2025). https://doi.org/10.1039/D4EE05745G

[6] M. R. Mirzaei, A. Ajdari and S. P. Woo, Spatial and temporal distribution pattern and biomass trend of flathead slipper lobster, Thenus orientalis (Lund, 1793) from Gulf of Oman, *Int. J. Aquat. Res. Environ. Stud.*, **3**(1), 27–36 (2023). https://doi.org/10.70102/IJARES/V3I1/3

[7] X. Wang, X. Shi, S. Yin, J. Zheng, Y. Song and H. Sun, Bioinspired material for high-performance photocatalytic systems, ACS Mater. Lett., **6**(8), 3770–3793 (2024). https://doi.org/10.1021/acsmaterialslett.4c00041

[8] M. Tahmasebi, F. Ehya and G. R. Paydar, Geochemical and geological studies of oil shales in Ab Kaseh section, Kouhrang County, Chaharmahal and Bakhtiari Province, Iran, Arch. Tech. Sci., **1**(32), 75–92 (2025). https://doi.org/10.70102/afts.2025.1732.075

[9] M. S. Akhtar, M. T. Naseem, S. Ali and W. Zaman, Metal-based catalysts in biomass transformation: from plant feedstocks to renewable fuels and chemicals, Catalysts, **15**(1), 40 (2025). https://doi.org/10.3390/catal15010040

[10] Y. Zhang and J. Liu, Bioinspired electrocatalytic NAD(P)H regeneration, Curr. Opin. Electrochem., **46**, 101506 (2024). https://doi.org/10.1016/j.coelec.2024.101506

[11] L. Mohammad Abbas, K. S. Shivraj, U. Perachi Selvi, R. Balasubramani and S. Dhanasekaran, Exploring the relationship between academic science and economics through biofuel research: a scientometric analysis, Indian J. Inf. Sources Serv., **14**(1), 85–92 (2024). https://doi.org/10.51983/ijiss-2024.14.1.4112

[12] R. Gupta and A. K. Pal, Bioinspired photo-driven hydrogen evolution systems based on hydrogenases and their mimics, Sustain. Energy Fuels, **8**(20), 4709–4751 (2024). https://doi.org/10.1039/D4SE00423J