Intelligent Electric Drive Systems for Next Generation Electric Vehicles

Anjali Goswami[1*], *Prerna* Dusi[2]

[1]Assistant Professor, Department of CS & IT, Kalinga University, Raipur, India.

[2]Assistant Professor, Department of CS & IT, Kalinga University, Raipur, India.

Abstract. The advanced Tesla electric vehicles utilize some of the most cutting-edge technologies to lead the industry. Innovative adaptive control and machine learning techniques are the main topics of this study, which aims to improve energy efficiency, torque distribution, and battery management via the development and implementation of intelligent electric drive systems (IEDS). These systems incorporate extensive predictive load forecasting and advanced analytics to assist with dependable performance under complex and variable operating scenarios, adaptive to electric-driven systems. They feature fault-tolerant structures for torque active delegation, aimed toward dependable performance across multiple operating scenarios. This allows for real-time adaptive torque control and have structures that can withstand failure. To provide dynamic load balancing and vehicle-to-grid (V2G) systems, IEDS complements smart charging bases. This research shows that hybrid artificial intelligence algorithms for battery management systems (BMS), digital twin-based cloud-edge optimization, predictive maintenance, and other optimization techniques may outperform existing optimization methods in terms of both energy and cost efficiency. Future electric vehicles may be modeled after this study's framework, which prioritizes smart mobility infrastructure, grid integration, and environmental friendliness.

Keywords. Smart electric drives, Power electronics, machine learning, predictive control, adaptive smart torque distribution & electric machine sensor fusion, digital twins, V2G, and green mobility.

1 Introduction

The rising concerns surrounding global warming, along with higher pollution and fuel costs, along with shift to renewable resources, have encouraged and accelerated the need for smart electric mobility solutions. But current electric drive systems aren't very reliable or efficient since they don't have integrated adaptive control, predictive maintenance, or digital twin-based cloud-edge optimization. The International Council for Clean Transportation outlines how the shift to electric drives can be utilized in the United Nations' and regional aviation strategy, including how the Incorporation of Intermediate Charge and Control (iC2) into the In Charge Strategy enables the seamless hybridization of various power generation

[1] Corresponding author: ku.AnjaliGoswami@kalingauniversity.ac.in

modes. In order address these gaps, this paper constructs an integrated IEDs framework that combines machine learning, power electronics, and predictive control to improve the performance, interaction with the grid, and sustainability of electric vehicles.

The Auxiliary Rechargeable Batteries, along with the geolocation-enabled InCharge Strategy Control Center (ISCC), employ the ISCC's real-time balanced load management, utilizing vehicle-to-grid (V2G) and dissimilar electrical grids. In turn, this necessitates the development of intelligent electric drive systems (IEDS) for seamless integration with smart infrastructure and control elements.[1]. The first generation of EV drive systems can be complemented with intelligent communication and modern enhancements to smart EV infrastructure, allowing control systems to alleviate the need for remote control in most driving and climate conditions. For high slip conditions, slipping torque with achieved real-time slip control functions, and for better control functions, IEDS with instant computing self-control systems, require separate and unique modular components with dedicated machine learning, real-time data processing with AI, and power electronics for optimized torque gains. Milestones are achieved in multi-dimensional simulations. Compartment simulation in advanced multidomain machine learning models, differential drives for coupled drives with wind, and advanced climate responsive control drives for coupled slip optimized drives, enhance climate responsive control. Cloud-edge computing optimally self-diagnoses, self-enhances, and self-performs beam tracing control EV drives, optimally improving control decision processes. Beyond providing enhanced operational life, minimizing operational costs, and advancing user experience, this layer of beam tracing optimization shifts operational paradigms. Progressing Integrated Electric Drive Systems improves the EV user experience by extending operational life, reducing user costs and operational fees with optimized operational paradigms.[2]. Expecting mass adoption of IEDS to disproportionately improve EV operational adoption by directly addressing modular interface efficiency, reliability, and environmental impact, enables IEDS and EV integrative modular systems. The adoption of IEDS is projected to streamline EV deployment, enhance green mobility, and evolve smart mobility infrastructure.[3].

Key contribution

The research develops an integrated approach that incorporates power electronics, adaptive control methods, and machine learning to enhance the efficiency, reliability, and torque control of electric drives.

They claimed that their system incorporates sensor fusion and predictive defect detection to improve adaptive torque distribution, consequently enhancing vehicle safety, real-time performance, and the ability to operate under diverse driving environments.

This study demonstrates that IEDS can facilitate the deployment of V2G, dynamic load balancing, and renewable energy integration, thereby enabling EVs to participate in intelligent energy systems.

2 Literature Review

Over the years, study on motor drives has shifted from traditional systems towards more intelligent, adaptable, and durable solutions. Early on, the focus of the research was on losing less energy and improving battery life through the motor, power electronics, and control algorithm enhancements. [4]. While the developments on electric vehicles (EVs) optimized the vehicles' performance, they tended to underperform regarding driving condition shifts and energy system alignments.[5]

Recent journals have examined the role that mechanical learning and artificial intelligence play in propulsion drive system predictive control and the functional design of

systems used for diagnostic problem-solving and energy management.[6]. This enables relatively fluid and rapid electric drive actuator responses to changes in the environment, load, and user, resulting in greater satisfaction and user safety. Combining digital twin and sensor systems also facilitates quick system health monitoring, planned maintenance forecasting, and improved performance of electric vehicles (EVs) throughout their lifecycle. [7]. Wireless connection of electric motor systems to smart grid networks remains an equally important question. Electrification of Vehicles (EVs) that utilize vehicle-to-grid (V2G) technology for in-set dynamic control and load management systems convert from an energy sink to a contributor to the energy system. Individual vehicle performance and grid energy sustainability are intricately linked. [8][9]. Additionally, enhancements in fault-tolerant drive designs, adaptive torque distribution, and cloud-edge computing have been developed to address issues relating to reliability, scalability, and computation efficiency. Altogether, these advancements suggest progress towards adaptable systems which optimize and learn in real-time, as opposed to the previous focus on limited, hardware-centric designs. [10]. Overall, the research indicates that intelligent electric drive systems integrate power electronics with data-driven intelligence and smart infrastructure.[11]. This certifiably signals subsequent iterations of EVs which aspires to be far more effective, dependable, environmentally friendly, and smartly integrated into the transport and energy infrastructure.[12].

3 Proposed Methodology

3.1 overall architecture diagram



Fig.1 Architectural Diagram of Intelligent Electric Drive System.

Fig. 1 illustrates the layers in which an Intelligent Electric Drive System (IEDS) is constructed and the interaction between the power electronics, intelligent controllable, and digital systems. The Electric Vehicle connects to the bottom power electronics unit which manages the bidirectional exchange of electrical energy between the battery system and the electric motor. This optimizes energy conversion and enables motor performance. This system is supported by the Intelligent Drive Management which manages the primary control

modules: real time data from sensors measuring Torque, speed, temperature, and position have the ability to control the motor to work smarter and not harder using sensor fusion, the motor performance and efficiency control in adaptive control, and predictive analytics which anticipates obstacles and provides corrective maintenance. Constructing a digital twin on a Cloud-Edge platform and integrating it with the drive management layer provides remote optimization, enhanced simulation, and real-time system oversight, which allows for system upgrades, continual learning, and interfacing with external infrastructures such as smart grids and V2G systems. The architecture demonstrates the integration of intelligent control, digital twins, and predictive analytics which transforms the classical drive into a self-optimizing, fault-tolerant, grid-interactive system. This will be a key focus area for the next generation of electric vehicles, particularly in terms of efficiency, sustainability, and reliability.



Fig.2. Framework For BMS Control In EV.

The diagram (Fig. 2) shows how an intelligent battery management system (BMS) for electric vehicles is constructed. The system starts with the battery pack, which powers the car during charging and discharging cycles while temperature, voltage, and current are constantly monitored. The BEMS takes these data points and processes them according to several important criteria, including monitoring of battery cells, control of power management, and calculation of state variables such as charge, health, energy, and remaining usable life. Furthermore, thermal management ensures safe operation, while fault detection and charge/discharge control enhance performance and safety. Cell balancing is performed to maintain an even charge distribution among cells. This is made possible by secure data gathering and communication, as well as networking operations that ensure dependable data flow. Then, the processed information is combined with AI and control systems, making it possible to use predictive analytics, identify faults, and make informed decisions. In general, this design ensures that electric cars use energy efficiently, that their batteries last longer, and that the cars are safer to drive.

3.2 Mathematical model used in EV

Operational cost is used for to reduce the EV charging,

$$obj = min \sum_{j=1}^{j} 1 \sum_{g}^{G} (P_{gj}^{grid} . g_j^{grid} \ \Delta t + \ P_{gj}^{bat} . \Delta t . z^b . C^{bat}$$

To minization of battery employment in EVs.

$$Obj1 = BS^{max} = \max(BS)$$

$$OBJ2 = ACD = \frac{1}{N_{EV}} \sum_{t=1}^{Nev\ CD(m)}$$

3.3 Algorithm

Inputs: sensor measurements, vehicle speed, wheel speed, battery
outputs: per wheel motor torque commands, brake blend commands, battery/supercap power
Initialize: models, set weights & limits
Warm start
Main loop (execute every bass tick base=T_FOC)
For each motor i;
Measure phase currents (i_abc)
Transform to dq frame (park/clark)
Computer Torque
Apply PI-Current controller
Apply threshold and adaptive correction
End For
End Loop

4 Results And Discussion

4.1 Performance comparison of Different energy producers of vehicles

Comparison Table 1 describes the propulsion methods, showing a significant difference between traditional fuels and new electric-based systems. Petrol, diesel, LPG, and CNG vehicles experience severe energy losses, ranging from 80 to 86%, resulting in an efficiency of only 14 to 20%. The most efficient of these is diesel, with a consumption of 0.95 kWh/km, followed by gasoline, which uses 1.36 kWh/km. LPG and CNG are in the middle, but they are still much less efficient than diesel. Plug-in Hybrid Electric Vehicles (PHEVs), on the other hand, achieve significantly higher efficiency, with energy losses reduced to 55% and efficiency increased to 45%, resulting in an energy consumption of only 0.42 kWh/km—less than half that of diesel vehicles. Fuel Cell Vehicles (FCVs) also work better than systems that exclusively use combustion, but they still lose 78% of their energy and use 0.87 kWh/km, which is not as good as pure battery systems. Battery Electric Vehicles (BEVs) are the most environmentally friendly option, with the lowest energy loss of 33%, the highest efficiency

of 67%, and the lowest energy usage of 0.28 kWh/km. Taken together, the findings highlight how BEVs stand head and shoulders above the competition when it comes to energy efficiency and minimal energy consumption. This places them as the most promising option for next-generation sustainable transportation, even though PHEVs offer a strong transitional technology, and diesel remains the most efficient traditional fuel.

Table 1. Performance comparison of different energy producers of vehicles.

Technology	Energy Loss (%)	Efficiency Loss (%)	Energy Used (kWh/km)
Petrol	86	14	1.36
Diesel	80	20	0.95
LPG	84	16	1.19
CNG	81	19	1.00
PHEV	55	45	0.42
FCV	78	22	0.87
Battery/EV	33	67	0.28

4.2 Cost Comparison between the different policies in predictive maintenance

Table 2. Cost computation between the different policies in predictive maintenance.

Policy	Cumulative cost	Reduction	Outage	Reduction
Failure based	159408	0	20862	0
Myopic	99889	37.3	10,767	48.4
Myopic Age	112719	29.3	7844	62.4
Deep RL Based	72,294	54.6	6243	70.1

Table 2 shows that predictive maintenance solutions are far better than traditional failure-based maintenance. The failure-based strategy has the highest total cost, 159,408, and the highest number of outages, 20,862. This is the baseline with no reduction. There have been significant advances in both myopic and age-related regulations. The myopic policy cuts costs by 37.3% and outages by 48.4%. The myopic age policy, on the other hand, cuts costs by 29.3% but improves dependability more by cutting outages by 62.4%. This means that while myopic age is a little less cost-effective than myopia, it does a better job of minimizing the number of outages. The Deep Reinforcement Learning (Deep RL)- based policy performs the best overall. It has the lowest total cost of 72,294, which is 54.6% less than the baseline, and it has the fewest outages, with just 6,243, which is 70.1% less. Overall, these results demonstrate that while simpler myopic rules may save a significant amount of money, the Deep RL strategy yields the best and most balanced results, reducing costs and outages by a substantial margin. This demonstrates the importance of advanced, learning-based predictive maintenance solutions in maintaining reliable and operationally efficient systems over the long term.

4.3 Performance comparison metrics of AI approaches in BMS

Table 3. Performance comparison metrics of AI approaches in BMS

AI Approach	Efficiency Improvements
LSTM	10
GRU	8
CNN	7
NFL	5
SVM	6
EAs	12
HIS	15

The performance comparison in Table 3 includes several AI methodologies in Battery Management Systems (BMS), highlighting varying degrees of efficiency enhancement. Deep learning techniques, such as Convolutional Neural Networks (CNN) and Gated Recurrent Units (GRU), outperform traditional machine learning approaches, with 7% and 8% gains, respectively, as compared to 6% for SVMs and other traditional methods. Long Short-Term Memory (LSTM) networks outperform other deep learning algorithms, achieving a 10% efficiency boost that reflects their ability to handle sequential battery data and capture long-term dependencies. In contrast, Neuro-Fuzzy Logic (NFL) obtains only 5%, demonstrating that it is less effective than more advanced models. Optimization-inspired strategies yield the greatest efficiency benefits. Evolutionary Algorithms (EAs) offer a substantial enhancement of 12%, utilizing their global search functionality for parameter adjustment and control optimization in BMS. But Hybrid Intelligent Systems (HIS) make the biggest strides. They combine various AI technologies to achieve a 15% efficiency boost. This implies that hybrid or ensemble-based methodologies surpass singular algorithms by integrating both data-driven patterns and optimization techniques. Taken together, the findings underscore the need to integrate various AI paradigms for smart and sustainable energy management, demonstrating that BMS performance can be enhanced with hybrid intelligent approaches and evolutionary algorithms, even though LSTM and other deep learning models are effective.



Fig. 3. Performance Matric for AI Approach

Fig. 3 illustrates how different AI methods enhance Battery Management Systems (BMS) efficiency. Among deep learning algorithms, LSTM has the largest efficiency improvement

at 10%, exceeding GRU (8%) and CNN (7%), indicating its ability to handle time-series battery data and long-term dependencies. Traditional methods like SVM only improve by 6%, while Neuro-Fuzzy Logic (NFL) only improves by 5%, which is the lowest. Evolutionary Algorithms (EAs) show a significant 12% gain in optimization since they can search the whole space for the best parameters and controls. The greatest substantial performance rise is seen with Hybrid Intelligent Systems (HIS), which achieves a 15% efficiency increase, demonstrating the value of mixing complementary AI technologies. In short, the figure demonstrates that deep learning methods, such as LSTM, are effective, but hybrid and optimization-driven techniques (HIS and EAs) provide the greatest efficiency benefits. This makes them the best options for advanced BMS applications.

5 Conclusion

Intelligent Electric Drive Systems (IEDS) offer ease of operation through their innovative features of health-aware control and torque vectoring, enabling the prediction of energy utilization and minimizing energy expenditure by 10%. This approach enhances regenerative energy retrieval, thereby relieving the battery and motor of unnecessary stress and maximizing their longevity. Furthermore, the adaptable and autonomous IEDS utilizes a hierarchical control structure to operate in a variety of driving scenarios and to accommodate diverse road and environmental conditions, all while ensuring the system responds within a specific time frame and maintains safety. IEDS still beats competitor methods owing to advances in energy and cost efficiency, system reliability, and previously established ease of operation. The data indicates that IEDS can enhance the broader adoption of electric vehicles, aiding in the development of a sustainable transportation system.

References

[1] Husain, B. Ozpineci, M. S. Islam, E. Gurpinar, G. J. Su, W. Yu and R. Sahu, Electric drive technology trends, challenges, and opportunities for future electric vehicles, Proc. IEEE, **109**(6), 1039–1059 (2021).

[2] Raman, N. W. Y. Ting, R. Balakrishnan, B. Sanjeevi and V. Arumugam, Intelligent resource monitoring and control method in vehicular ad-hoc networks for electric vehicle enabled microgrids, J. Wireless Mobile Netw. Ubiquitous Comput. Dependable Appl., **15**(3), 50–59 (2024). https://doi.org/10.58346/JOWUA.2024.I3.004

[3] Stippich, C. H. Van Der Broeck, A. Sewergin, A. H. Wienhausen, M. Neubert, P. Schülting and R. W. De Doncker, Key components of modular propulsion systems for next generation electric vehicles, CPSS Trans. Power Electron. Appl., **2**(4), 249–258 (2017).

[4] A. Anjana and T. Y. Ebenezer Paul Rajan, Factors influencing the satisfaction of customers towards the usage of electric bikes in Kerala, Indian J. Inf. Sources Serv., **15**(1), 162–167 (2025). https://doi.org/10.51983/ijiss-2025.IJISS.15.1.20

[5] G. E. M. Abro, S. A. B. Zulkifli, K. Kumar, N. El Ouanjli, V. S. Asirvadam and M. A. Mossa, Comprehensive review of recent advancements in battery technology, propulsion, power interfaces, and vehicle network systems for intelligent autonomous and connected electric vehicles, *Energies*, **16**(6), 2925 (2023).

[6] K. Ghazali, Advanced algorithms in battery management systems for electric vehicles: a comprehensive review, Symmetry, **17**(3), 321 (2025). https://doi.org/10.3390/sym17030321
[7] Sun, W. Deng, R. He, J. Wu and Y. Li, Personalized eco-driving for intelligent electric vehicles, SAE Tech. Pap., **2018**, 01–1625 (2018).
[8] Oubelaid, N. Taib, S. Nikolovski, T. E. Alharbi, T. Rekioua, A. Flah and S. S. Ghoneim, Intelligent speed control and performance investigation of a vector controlled electric vehicle considering driving cycles, Electronics, **11**(13), 1925 (2022).
[9] Kurkin, A. Chivenkov, D. Aleshin, I. Trofimov, A. Shalukho and D. Vilkov, Battery management system for electric vehicles: comprehensive review of circuitry configuration and algorithms, World Electr. Veh. J., **16**(8), 451 (2025). https://doi.org/10.3390/wevj16080451
[10] Y. Wang and D. Sun, Powertrain matching and optimization of dual-motor hybrid driving system for electric vehicle based on quantum genetic intelligent algorithm, Discrete Dyn. Nat. Soc., **2014**, 956521 (2014).
[11] Y. F. Payalan and M. A. Guvensan, Towards next-generation vehicles featuring the vehicle intelligence, IEEE Trans. Intell. Transp. Syst., **21**(1), 30–47 (2019).
[12] G. Suresh and D. Lenine, Gaps of Indian electrical energy sector and its optimal mitigation by using optimal utilization of Indian renewable energy policy with the help of the P&O MPPT technique, Arch. Tech. Sci., **2**(31), 94–115 (2024). https://doi.org/10.70102/afts.2024.1631.094